BOSTITCH®

Industrial Tools & Fasteners

Pallets, Crating, Fencing
Upholstered Furniture
Case Goods
Manufactured Housing
Mattress Assembly
Millwork
Carton and Bag Closure
Specialty Industrial Tools

BOSTITCH®
INDUSTRIAL

Our tools have been dropped, dragged, shaken and even frozen under sub-zero conditions. Why go to extremes? At Bostitch® Industrial we know that you demand superior performance in extreme industrial work environments. At the end of the day, you know that Bostitch® Industrial is up to your challenge; you can depend on us... no excuses.

IMPORTANT
SAFETY INFORMATION

IMPORTANT – READ CAREFULLY

You, and others working around you, can be seriously injured by fastener driving tools if you do not follow the instructions provided on the tool and in the operator's manual. Used properly, these tools provide easy, safe, and efficient methods for driving nails and staples for all kinds of construction projects.

REFER to your Operator's Manual, Parts List, or call Bostitch® Industrial Customer Service at: 1-800-832-3080 if any of the terms used below are unfamiliar to you.

EYE PROTECTION which conforms to ANSI Z87.1 specifications and provides protection against flying particles both from the FRONT and SIDE should ALWAYS be worn by the operator and others in the work area when connecting to air supply, loading, operating or servicing this tool. Eye protection is required to guard against flying fasteners and debris, which could cause severe eye injury.

THE CONTACT OR SEQUENTIAL TRIP

Bostitch offers two types of triggers for pneumatic tools: Contact Trip (black trigger) and Sequential Trip (silver-gray trigger). Each trigger has specific advantages. For example, the Contact Trip is best suited for high-volume, rapid nailing or stapling where exact placement of the fastener is not important.

The Sequential Trip is best suited for applications where rapid nailing is not required or where the exact placement of the fasteners is important. You should evaluate your construction project to determine which trigger type is best for you.

CONTACT TRIP

A Bostitch® Industrial tool with the Contact Trip (black trigger) will drive a nail whenever both the trip and the trigger are depressed at the same time.

The tool can be used to rapidly drive nails by holding the trigger pulled and repeatedly bumping the trip against the work to be nailed (Bump Firing). A nail is driven each time the trip is bumped against the work.

The Contact Trip (black trigger) will not prevent a nail from being accidentally driven if the trigger is held, pulled and the trip is bumped against any object or person. Never hold or carry the tool with your finger on the trigger unless driving fasteners.

The Contact Trip (black trigger) can also be operated by holding the tool against the work with the trip depressed and then pulling the trigger (Place Nailing).

When using a Contact Trip for Place Nailing, the tool may bounce due to recoil, and if the tool is allowed to recontact the work surface while you are holding the trigger, a second nail will be driven. The operator should allow the tool to recoil far enough to release the trip and avoid a second cycle. Don't push the tool down extra hard; let the tool do the work.

SEQUENTIAL TRIP

The Sequential Trip (silver-gray trigger) offers a positive safety advantage since it will not accidentally drive a nail if the tool is bumped against any surface or while the operator is holding the tool with the trigger pulled.

It also allows Place Nailing without the possibility of driving a second nail on recoil as described under "Contact Trip."

The Sequential Trip (silver-gray trigger) gets its name from the "sequence" required to operate the tool. To drive a nail, the operator must first depress the trip against the work and then pull the trigger. To drive a second nail, the operator must lift the tool from the work, release the trigger, and then repeat the above sequence.

If further information is required, call Bostitch® Industrial Customer Service at 1-800-832-3080.

www.BostitchIndustrial.com
orders@BostitchIndustrial.com
Phone: 1-800-832-3080   FAX: 1-800-842-9360

TABLE OF CONTENTS

This catalog was designed to highlight the complete line of Bostitch® Industrial tools and collated fasteners specifically suited for a particular industry.

Nationwide Expert
SERVICE & REPAIR   Pages 4, 5, 18

Nationwide Expert SERVICE & REPAIR

SouthernCarlson
Fastening. Packaging. Service.

Contact your sales professional
for locations or visit
www.SouthernCarlson.com

Pallet Plus™

Revolutionary Nail Technology. Ultimate Pallet Performance.

Why Pallet Plus™ is the Industry Leader for Pallet Nails

Pallet Plus™ is a series of premium performing fasteners from **Bostitch® Industrial.** Rigorous tests were performed and the overwhelming results confirmed **Pallet Plus™** would revolutionize the pallet industry.

At **Bostitch® Industrial** we pride ourselves on our ability to deliver new and exciting fastener technology not only for today but for the next 100 years.

264% More Protection from End Board Impact

17% Increase in Diagonal Rigidity

40% Greater Shear Resistance

35% Increase in Withdrawal Performance

15% Greater Resistance to Pull-Through

End Board Impact Resistance
- **264% Greater** resistance to pallet failures caused by forklift impact

Diagonal Rigidity
- **17% Increase** in diagonal rigidity of pallet

Shear
- Oak-**52% Greater**
- Poplar-**41% Greater**
- Spruce, Pine, Fir-**40% Greater**

Withdrawal
- Oak-**38% Increase**
- Poplar-**37% Increase**
- Spruce, Pine, Fir-**35% Increase**

Pull Through
- Oak-**22% Greater**
- Poplar-**14% Greater**
- Spruce, Pine, Fir-**25% Greater**

Test results reflect increase in performance compared to standard 2" x .099" screw shank pallet nail.

Bostitch® Industrial Featured Pallet Plus™ Item

Pallet Plus™ .084" Collated Nails

Your replacement for standard .099" pallet nails. Our patented nail geometry delivers equivalent performance to standard .099" pallet nails using a shorter and thinner nail. Also take advantage of the 20% lighter N64084-1 tool.

- **Equal Performance vs. Standard .099" Collated Pallet Nails**
- **Use a Lighter Tool**
- **Increase Productivity**
- **Reduce Operator Fatigue**

Pallet Plus™
The Results Are Decisive

Fat Head
- 19% larger head
- Maximizes shear and pull through performance
- Foundation for greater pallet end board impact resistance and diagonal rigidity

Industry Leadership
- International provider of collated fastener solutions to the pallet industry
- Serving industry since 1896
- Introduced first coil nailer and nails in 1965

3 Patents Pending.
- Innovative nail design
- Ultra performance
- Recognized product differentiation

"No Voids" Shank Technology
- 100% deep screw in active plane area
- No voids for collation wire
- Optimizes withdrawal performance

Royal Purple Coating
- Maximizes depth of drive
- Polymer coating composition optimized for maximum anti-withdrawal performance
- Colored for easy identification

Made to Fit
- Bostitch® Industrial N70CB, N86C, N89C-1P

Precision Point
- Available in Blunt Diamond and Blunt Chisel
- Reduces splitting in hardwoods

Bostitch® Industrial offers an extensive line of hard-working, long-lasting industrial strength pneumatic tools.

Pallet Repair and Assembly:

IC60-1 Coil Nailer

N64084-1 Coil Pallet Nailer

N64099-1 Coil Pallet Nailer*

N89C-1P Pallet Nailer

N70CB-1 Angle Coil Nailer*

N70CB-PAL Machine-Mount Pallet Nailer*

N80CB-1 Coil Pallet Nailer**

N80CB-PAL Machine-Mount Pallet Nailer**

N400C-1 Coil Pallet Nailer*

650S4-1 Stapler

650S5-1 Stapler

863S4-1 Stapler

CF15-2 Corrugated Tool

*Some restrictions apply **Canada only

650S4-1 Reattaching Deck Board

CF15-2 Pneumatic corrugated tool repairing split stringer

There's Bostitch® Industrial fastener for every application. Check out our Fastener - Tool Selection guide on pages 40 - 44 in the back of the catalog.

BOSTITCH®

INDUSTRIAL

Crate Assembly:

IC60-1 Coil Nailer
N70CB-1 Angle Coil Nailer*
N80CB-1 Coil Nailer**
N64084-1 Coil Nailer
N64099-1 Coil Nailer*
N400C-1 Coil Nailer*
N89C-1P Coil Nailer
438S2-1 Wide Crown Stapler
538S4-1 Stapler
538S5-1 Stapler
650S4-1 Stapler
650S5-1 Stapler
750S4-1 Stapler
750S5-1 Stapler
863S4-1 Stapler

Fence Assembly:

N64084-1 Coil Nailer
N80CB-1
HFP9 Fence Plier
*Some restrictions apply **Canada only

750S4-1 Assembling crate face-frame

N400C-1* Nailing mat to block pallet

Machine mounted nailer

IC60-1 Coil nailer fastening fence header board

HFP9 Attaching tensioning wire to chain-link fence with 9 gauge aluminum hog rings

IC60-1

Box Frame Nailer

Features:
- Uses wire collated nails
- Lightweight, compact design
- Durable cast aluminum frame and cap
- Quick-open composite canister survives falls
- Adjustable exhaust to direct air away from user
- Side wear guards and bumpers protect tool from damage
- Rubber grip for improved comfort and control
- 360 degree directional exhaust

Applications:
- Pallets assembly and repair
- Fence panel assembly
- Crate assembly

Description:
- Tool Weight: 5.7 lbs.
- Driving Power: 445 inch lbs. @ 100 psi
- Magazine Capacity: 300 to 350 depending on nail size
- 1" to 2-1/4" (2d to 7d)

|		
Screw		1 1/2" 1 3/4"
Ring		1" 1 1/4" 1 1/2" 1 3/4" 2" 2 1/4"
Smooth		1 1/4" 1 1/2" 1 3/4" 2" 2 1/4"

Available in: Plain, galvanized, stainless steel, aluminum

FASTENERS: AC, C, FC SERIES

N400C-1*, N100C-1⁺

Hardwood Pallet, Crate Nailer

Features:
- Drives wire collated nails from .099" to .148" in diameter
- Secondary handle, rubber grip and integral balancer mounting point in cap

Applications:
- Block pallet assembly
- Hardwood Crate and Pallet Assembly

Tool Description:
- Tool Weight: 11.6 lbs.
- Driving Power: 1450 inch lbs. @ 100 psi
- Magazine Capacity: 225 to 300 depending on nail size

15° Coil Nail

Screw		3" 3 1/4" 4"
Ring		2 1/2" 3" 3 1/4" 4"
Smooth		2 1/2" 3" 3 1/4" 3 1/2" 4"

Available in: Plain, galvanized, stainless steel

FASTENERS: AC, C, FC SERIES

## N64084-1, N64099-1*

Pallet, Crate, Fence Nailer

Features:
- Uses wire collated nails
- Oversized canister opens completely for easy reloading
- Tool-free adjustable exhaust
- Oversized bore for driving

N64084-1
.084" Pallet Plus™ nails

N64099-1
.099" Pallet Plus™ and WB nails

Applications:
- Crate frames, medium duty pallet assembly and repair
- Fence panel assembly
- Picket assembly using aluminum nails

Tool Description:
- Tool Weight: 6.1 lbs.
- Driving Power: 560 inch lbs. @ 100 psi
- Magazine Capacity: 225 to 350 depending on nail size
- 1-1/4" to 2-1/2" (3d to 8d)

Screw		1 1/4" 1 1/2" 1 3/4" 2" 2 3/16" 2 1/2"
Ring		1 1/4" 1 1/2" 1 3/4" 2" 2 3/16" 2 1/2"

Available in: Plain, galvanized, stainless steel, aluminum**

**Aluminum nails require door conversion kit (Item#112670)

FASTENERS: AC, C, ACP, FC SERIES

N70CB-1*

Heavy Duty Pallet Nailer

Features:
- Uses wire collated nails
- Angled coil design for high operator visibility
- Quick loading canister
- Better balance for operating ease
- 360 degree directional exhaust

Applications:
- Heavy duty pallet assembly

Tool Description:
- Tool Weight: 7.9 lbs.
- Driving Power: 738 inch lbs. @ 100 psi
- Magazine Capacity: 225 to 300 depending on nail size
- 1-1/2" to 2-3/4" (4d to 9d)

Screw		1 1/2" 1 3/4" 2" 2 3/16" 2 3/4"
Ring		1 1/2" 1 3/4" 2" 2 3/16" 2 3/4"
Smooth		1 1/2" 1 3/4" 2" 2 3/16" 2 3/4"

Available in: Plain, galvanized, stainless steel, aluminum**

**Aluminum nails require door conversion kit (Item#112670)

FASTENERS: AC, C, FC, FC Pallet Plus™ SERIES

N70CB-PAL*, N80CB-PAL

Machine Mount Pallet Nailer

Features:
- Uses 15 degree wire collated nails
- 360 degree directional exhaust

Applications:
- Machine mount nailer

Tool Description:
- Magazine Capacity: 225 to 300
- N70CB-PAL Driving Power: 880 inch lbs.
- N80CB-PAL Driving Power: 738 inch lbs.

Available in: Plain, galvanized, Stainless Steel

FASTENERS: AC, C, FC, FC Pallet Plus™ SERIES

*Some restrictions may apply. +Special order item.

BOSTITCH®

INDUSTRIAL

N89C-1P, N80CB-1* *(for Canada only)*

Heavy Duty Pallet, Fence Nailer

Features:
- Quick-open composite canister survives falls
- Drives wire collated nails .099"-.148"
- Durable aluminum housing
- Rubber comfort grip
- 360 degree directional exhaust

Applications:
- Heavy duty block pallet assembly
- Heavy duty picket fence assembly

Tool Description:
- Tool Weight: 8.1 lbs. / 8.4 lbs.
- Driving Power: 1050 inch lbs. / 880 inch lbs.
- Magazine Capacity: 225 to 300 depending on nail size

15° Coil Nail

Screw				3"	3 1/4"
Ring		1 3/4"	2" 2 1/4"	3"	3 1/4"
Smooth		1 1/2" 1 3/4" 2" 2 1/4"		3"	3 1/4"

Available in: Plain, galvanized, stainless steel

FASTENERS: AC, C, FC, FC Pallet Plus™ SERIES

538S4-1, 538S5-1

Medium Duty Crate Stapler

Features:
- Anti-Jam™ magazine permits staples to exit nose without jamming
- Long narrow nose for improved line of sight
- Adjustable trip for positive staple depth control
- Long magazine kit available
- 360 degree directional exhaust

Applications:
- Light and medium duty crate framing and sheathing

Tool Description:
- Tool Weight: 4.7 lbs.
- Driving Power: 260 inch lbs. @ 100 psi
- Magazine Capacity: 160
- Long Magazine: 300 +

538S4-1: 16 Gauge 3/8" to 1-1/2" leg
538S5-1: 16/17 Gauge 1/2" to 2" leg

16-Gauge S4 Staple

1/2" | 3/8" 3/4" 7/8" 1" 1 1/8" 1 1/4" 1 3/8" 1 1/2"

16-Gauge S5 Staple

7/16" | 1/2" 3/4" 7/8" 1 1/8" 1 1/4" 1 3/8" 1 1/2" 1 5/8" 2"

FASTENERS: 16S4, S5 STAPLES

## 650S4-1, 650S5-1, 863S4-1

Heavy Duty Pallet, Crate Stapler

Features:
- Anti-Jam™ breathing magazine permits staples to exit nose without jamming
- Long magazine kit available
- 360 degree directional exhaust

Applications:
- Heavy duty pallet manufacturing and repair
- Heavy duty crate framing

Tool Description:
650S4-1
- Tool Weight: 5.3 lbs.
- Driving Pwr: 465 inch lbs. @ 100 psi
- Magazine Capacity: 160
- Long Magazine: 300 +
- S4 and S5: 1-1/2" to 2" leg

850S5-1
- Tool Weight: 5.9 lbs.
- Driving power: 570 inch lbs.
- Magazine Capacity: 160
- Long Magazine: 300 +
- 1-1/2" to 2" leg

863S4-1
- Tool Weight: 5.7 lbs.
- Driving Pwr: 570 inch lbs. @ 100 psi
- Magazine Capacity: 160
- Long Magazine: 260
- 1-1/2" to 2-1/2" leg

16-Gauge S4 Staple

1/2" | 1 1/2" 1 3/4" 1 5/8" 2"

16-Gauge S5 Staple

7/16" | 1 1/2" 1 3/4" 1 5/8" 2"

FASTENERS: 16S4, S5 STAPLES

CF15-2

Pallet Stringer Repair

Features:
- Powerful to provide full penetration of stringers
- 360 degree directional exhaust

Applications:
- Repairing and strengthening split pallet stringers

Tool Description:
- Tool Weight: 6.58 lbs.
- Driving Power: 433 inch lbs.
- Magazine Capacity: 108

1"

3/8" 09
1/2" 12
5/8" 15

Available in: Aluminum

HFP9

Wire Fence Tool

Features:
- Allows collated hog rings to feed directly into the jaws
- Magazine pivots, allowing the tool to reach into difficult areas to fasten tension wire
- 360 degree directional exhaust

Applications:
- Fastening tensioning wire, signs to fence, stitching butt ends, and repair

Tool Description:
- Tool Weight: 1.2 lbs.
- Magazine Capacity: 25 rings

1 3/16" | 7/16"

Available in: Aluminum

FASTENER: RING09AL25

To increase productivity, it takes a quality craftsman and the right tool for the right job. Bostitch® Industrial is your partner every step of the way.

Furniture Frame Assembly:

538S4-1 Stapler
538S5-1 Stapler
650S4-1 Stapler
650S5-1 Stapler

Spring Assembly:

438S5-1 Stapler (will require
   438S5CLP KIT/ Nose Magnet)

Trim Assembly:

S32SX-1 Stapler
S32SL-1 Stapler
BT35B-1 Brad Nailer
BT50B-1 Brad Nailer

Packaging:

DS-3522 Box Closer
DS-3219 Box Closer
BTFP12180 Manual Box Closer
BTFP12181 Pneumatic Box Closer
BTFP12182 Box Closer
D62ADC Box Closer

Fabric to Wood:

21671B 71 Series Stapler
21671B-A Autofire
   Regular Magazine
21671B-ALM Autofire
   Long Magazine
21671B-LN Long Nose
21680B 80 Series Stapler
21680B-LN Long Nose
21697B 97 Series Stapler

Fabric to Wire:

TR201 D-Ring Spring Return
   Short Magazine Closing Tool
TR203 D-Ring Spring Return
   Long Magazine Closing Tool
TR315 D-Ring Air Return
   Long Magazine Closing Tool

438S5-1 Stapler applying anchor clip to chair rail

538S4-1 Stapler applying staples during knock-up

21671B Upholstery Tacker fastening fabric to seat cover with 71 series fine wire staples

216 Series

Fabric to Wood Assembly

Features:

21671B:
- Very lightweight, rugged, all metal construction, quiet, low air consumption

21671B-LN:
- Same as 21671B but with extended nose for greater visibility and access to hard-to-reach areas
- Long nose also helps prevent scarring and scratching of wood

21671B-A:
- 2-function trigger light squeeze for single fire mode; full squeeze for auto-fire mode
- Auto fire rate can be adjusted from 0 to 1600 staples/minute
- Same hand that activates trigger also opens magazine, allowing for new staple insertion with the free hand

21671B-ALM:
- Same as 21671B-A but w/long magazine (392 Staples) 21680B, 21680B-LN (long nose)
- Same as 21671B but fires 80 series staples
- 21697B Attaching double welt

Applications:
- Securing fabric to wood frame
- Pre-upholstery spring-up operation attach cardboard, webbing, Propex to frame
- Boat seating with stainless steel staples

Tool Description:

21671B
- Tool Weight: 1.8 lbs.
- Magazine Capacity: 196, 71 series staples

21697B
- Tool Weight: 1.9 lbs.
- Magazine Capacity: 156, 97 series staples

21671B-LN
- Tool Weight: 2.1 lbs.
- Magazine Capacity: 196, 71 series staples

21671B-A
- Tool Weight: 2.6 lbs.
- Magazine Capacity: 196, 71 series staples

21671B-ALM
- Tool Weight: 3.0 lbs.
- Magazine Capacity: 392, 71 series staples

21680B, 21680B-LN, 21680B-ALM
- Tool Weight: 1.8 lbs.
- Magazine Capacity: 156, 80 series staples

71 Staple

3/8" | 5/32" 1/4" 3/8" 1/2" | 3/16" 7/16" 5/16" 9/16"

80 Staple

1/2" | 1/4" 3/8" 1/2" | 5/32" 5/16" 9/16"

97 Staple

3/16" | 1/2" 5/8" | 3/8" 9/16"

FASTENERS: 71, 80 SERIES

438S5-1 Clip Kit

Spring Anchor Clip Stapler

Features:
- Ability to load OSK clip into tool prior to stapling
- Magnetic nose holds OSK clip in place for precise alignment of staple legs over clip holes
- Attachment of other sinous spring clips to frame seat and back rails

OSK Clip
- Polypropylene lined
- Edge embossed

Applications:
- Low volume over-the-rail spring clip placement or applications using plywood back posts

Tool Description:
- Tool Weight: 4.7 lbs.
- Magazine Capacity: 168 Staples
- Staple: 16 S5 Series, 1/2" to 1-1/2" leg

Also Available:
438S5CLPSKIT- For front magnet and steel stop for clip alignment.
438S5CLPTBKIT- For front and back magnets for top and bottom clip alignment.
438550SKCLPKIT- For long nose clips.

HR-OSK

Edge Embossing reduces contact of clip to spring

Down Turned Leg holds clip in place and reduces dependence on staples the spring rail will fail before the clip gives way

Staple Receiving Holes staples can be applied from the top or face of a rail

Detent positions and locks spring in place when clip is hammer closed

Polypropylene Lining insulates the spring from the clip

FASTENERS: 16 S5 SERIES

438S4-1, 438S5-1, 538S4-1, 538S5-1

Frame Assembly

Features:
- Anti-Jam™ magazine permits staples to exit nose without jamming
- Long narrow nose for increased visibility
- Adjustable trip for positive staple depth control
- Long magazine kit available

Applications:
- Attach steel bands to seat rails to support coil springs in 8-way hand tie
- Plywood frame assembly

Tool Description:
- Tool Weight: 4.7 lbs.
- Driving Power: 260 inch lbs. @ 100 psi
- Magazine Capacity: 160
  438S4-1: 16 Gauge 1/2" to 1-1/2" leg
  438S5-1: 16/17 Gauge 1/2" to 1-1/2" leg
  538S4-1: 16 Gauge 3/8" to 1-1/2" leg
  538S5-1: 16/17 Gauge 1/2" to 2" leg

16-Gauge S4 Staple

1/2" | 3/8" 3/4" 1 1/8" 1 3/8" | 7/8" 1" 1 1/4" 1 1/2"

16/17-Gauge S5 Staple

7/16" | 1/2" 3/4" 1 1/8" 1 3/8" 1 5/8" | 7/8" 1 1/4" 1 1/2" 2"

FASTENERS: 16 S4, S5 SERIES

450S2-1

Furniture Packaging / Frame Assembly Stapler

Features:
- Lightweight durable aluminum frame
- Anti-Jam™ magazine
- Power control valve, adjusts power by 30%
- Long-lasting molded rubber comfort grip
- Reduced height for stapling in tight areas
- Rear exhaust directs exhaust away from user and work surface
- High capacity, top-load magazine decreases reload time
- ESD-450S2-WS 450S2-1 with 22-1/2" extended handle available for easy fastening of boxes to pallets

Applications:
- Furniture packaging: corrugated boxes to wood
- Frame Assembly, bridge joints

Tool Description:
- Tool Weight: 4.6 lbs.
- Driving Power: 230 inch lbs. @ 100 psi
- Magazine Capacity: 160
- 1/2" to 2" leg

16-Gauge S2 Staple

1" | 1/2" 3/4" 1" 1 1/4" 1 1/2" 1 3/4" 2"

FASTENERS: 16 S2 SERIES

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

BOSTITCH®

INDUSTRIAL

650S4-1, 650S5-1

Furniture Frame Construction

Features:
- Anti-Jam™ magazine permits staples to exit nose without jamming
- Increased power to countersink staples into hardwood
- Long-lasting molded rubber comfort grip
- Long narrow nose for improved line of sight in precise applications

Applications:
- Furniture frame knock up

Tool Description:
- Tool Weight: 4.5 lbs.
- Driving Power: 340 inch lbs. @ 100 psi
- 16 Gauge 1" to 2" leg
- **650S4-1** Magazine Capacity: 160
- **650S5-1** Magazine Capacity: 171

16-Gauge S4 Staple

1/2"   1"   1 1/4"   1 1/2"   1 3/4"
             1 1/8"   1 3/8"   1 5/8"   2"

16/17-Gauge S5 Staple

7/16"   1"   1 1/4"   1 1/2"   1 3/4"
             1 1/8"   1 3/8"   1 5/8"   2"

FASTENERS: 16 S4, S5 SERIES

651S5-1

Medium Crown Stapler

Features:
- Depth-of-drive adjustment
- Selectable trigger
- Quick-release nose-piece for fast jam clearing

Applications:
- Furniture assembly

Tool Description:
- Tool Weight: 4.3 lbs.
- Driving Power: 405 in-lbs
- Operating Range: 70-120 PSI
- Magazine Capacity: 160
- 16 gauge 7/16" crown, 1" to 2" leg

16-Gauge S5 Staple

7/16"   1"   1 1/4"   1 1/2"   1 3/4"
             1 1/8"   1 3/8"   1 5/8"   2"

FASTENERS: 16 S5 SERIES

TR201, TR203, TR315

Attach Edge Roll to Border Wire

Features:
- TR201 Spring returned tool
- TR203 Spring returned tool long mag.
- TR315 High Speed air return, long mag. Magazine can be pivoted in 90° increments

Applications:
- Attaching edge roll to border wire

Tool Description:
- 15 ga. 3/4" D-Ring, 1/4" min. closure
- Short Magazine: 50 rings, 3.3 lbs.
- Long Magazine: 100 rings, 3.6 lbs.

15-Gauge D-Ring

3/4"   1/4"

Available in Basic Steel, galvanized, stainless

S32SL-1, S32SX-1

Production Finish and Trim Stapler

Features:
- Extreme-duty, high cycle design (requires oil)
- Composite frame/Aluminum magazine
- Narrow nose for improved line of sight

Applications:
- High production finish and trim
- Frame assembly - corner blocks, stretchers

Tool Description:

S32SL-1
- Tool Weight: 2.5 lbs.
- Driving Pwr: 160 inch lbs. @ 100 psi

S32SX-1
- Tool Weight: 2.4 lbs.
- Driving Pwr: 145 inch lbs. @ 100 psi

18-Gauge SX Staple

SX=7/32"
SL=5/16"

        1/2"   3/4"   1"   1 1/4"
           5/8"   7/8"   1 1/8"   1 3/8"
                    1 1/2"
                 (SX/SL150 ONLY)

FASTENERS: SX SERIES

BT35B-1, BT50B-1

Decorative Trim, Corner Block Nailer

Features:
- Extreme-duty, high cycle design (requires oil)
- Composite frame / Aluminum magazine
- Narrow nose for improved line of sight

Applications:
- Decorative molding, fine trim work

Tool Description:

BT35B-1
- Tool Weight: 2.4 lbs.
- Driving Pwr: 145 inch lbs. @ 100 psi

BT50B-1
- Tool Weight: 2.6 lbs.
- Driving Pwr: 165 inch lbs. @100 psi

18-Gauge Brad

BT50B
                                        1 3/4"
                                1 3/8" 1 9/16"   2"
        5/8"   1 3/16"   1 3/8"   1 3/4"
           3/4"   1"   1 1/4"   1 1/2 "   2"

BT35B
           3/4"   1 3/16"
        5/8"   1"   1 3/8"
           5/8"   1"   1 1/4"
              3/4"   1 3/16"

FASTENERS: BT SERIES

CASE GOODS

538S4-1 Stapler	438S4-1 Stapler	S32SL-1 Stapler	BT35B-1 Trim Nailer
538S5-1 Stapler	650S4-1 Stapler	S32SX-1 Stapler	BT50B-1 Brad Nailer
438S2-1 Stapler	650S5-1 Stapler	CF15-2 Corrugated Nailer	

1

18-gauge SX staples building drawers

CF15-2 Applying corrugated fastener to an angled butt joint

18-gauge brads fastening quarter round

Caseback being secured with 18-gauge SL staples

18-gauge brads applying trim

Need Expert Service & Repair for your long-lived Bostitch® Industrial Tools? Find a location near you! *(See pages 4-5, 18)*

538S4-1, 538S5-1

Medium Duty Structural Stapler

Features:
• Anti-Jam™ magazine permits staples to exit nose without jamming
• Long narrow nose for improved line of sight
• Adjustable trip for positive staple depth control
• Long magazine kit available
• 360 degree directional exhaust

Applications:
• Light and medium duty structural assembly

Tool Description:
• Tool Weight: 4.7 lbs.
• Driving Power: 260 inch lbs. @ 100 psi
• Magazine Capacity: 160
• Long Magazine: 300 +
538S4-1: 16 Gauge 3/8" to 1-1/2" leg
538S5-1: 16/17 Gauge, 1/2" to 2" leg

1/2"

3/8"   3/4"   1 1/8" 1 3/8"
        7/8" 1" 1 1/4" 1 1/2"

7/16"

1/2"   3/4"   1 1/8" 1 3/8" 1 5/8"
        7/8"   1 1/4" 1 1/2"   2"

FASTENERS: 16S4 STAPLES

438S2-1, 438S4-1

438S4-1 Shown

Packaging, Corner Connection Stapler

Features:
- Lightweight durable frame
- Reduced height for work in tight areas
- Long-lasting molded rubber comfort grip
- 30% adjustment in power with turn of valve
- Rear exhaust directs exhaust away from user and work surface
- Adjustable trip-positive staple depth control

Applications:
- S2 Packaging, corrugated containers to pallets
- S4 Corner connections, frames

Tool Description:
S2
- Tool Weight: 4.5 lbs.
- Driving Power: 230 inch lbs. @ 100 psi
- Magazine Capacity: 160
- 1/2" to 1-1/2" leg

S4
- Tool Weight: 4.05 lbs.
- Driving Power: 230 inch lbs. @ 100 psi
- Magazine Capacity: 160
- 1/2" to 1-1/2" leg

16-Gauge S2 Staple

1"
21/32"   1"   1 1/2"
1/2" 3/4"   1 1/4"

16-Gauge S4 Staple

1/2"
1/2" 3/4" 1" 1 1/4" 1 1/2"
5/8" 7/8" 1 1/8" 1 3/8"

FASTENERS: 16 S2, S4 SERIES

650S4-1, 650S5-1

Door, Window Frame Stapler

Features:
- Increases power to countersink staple into dense hardwood
- Long narrow nose for improved line of sight
- Long-lasting molded rubber comfort grip
- Adjustable exhaust directs exhaust away from user
- Adjustable depth guide

Applications:
- Door and window frames

Tool Description:
- Tool Weight: 4.5 lbs.
- Driving Power: 340 inch lbs. @ 100 psi
- 16 Gauge 1" to 2" leg
- **650S4-1** Magazine Capacity: 160
- **650S5-1** Magazine Capacity: 171

16-Gauge S4 Staple

1/2"
1" 1 1/4" 1 1/2" 1 3/4"
1 1/8" 1 3/8" 1 5/8" 2"

16-Gauge S5 Staple

7/16"
1" 1 1/4" 1 1/2" 1 3/4"
1 1/8" 1 3/8" 1 5/8" 2"

FASTENERS: 16 S2, S4 SERIES

CF15-2

Door, Cabinet Mitre Nailer

Features:
- Lightweight durable frame
- Powerful to provide full penetration of stringers

Applications:
- Joining door stiles, cabinet face frames
- Stile assembly, door window fabrication

Tool Description:
- Tool Weight: 6.58 lbs.
- Magazine Capacity: 128

Corrugated
For: CF15

1"
3/8"
1/2"
5/8"

FASTENERS: 16 S2, S4 SERIES

S32SL-1, S32SX-1

Production Finish and Trim Stapler

Features:
- Extreme-duty, high cycle design (requires oil)
- Composite frame/Aluminum magazine
- Narrow nose for improved line of sight

Applications:
- High production finish and trim
- Frame assembly - corner blocks, stretchers

Tool Description:
S32SL-1
- Tool Weight: 2.5 lbs.
- Driving Pwr: 160 inch lbs. @ 100 psi
S32SX-1
- Tool Weight: 2.4 lbs.
- Driving Pwr: 145 inch lbs. @ 100 psi

18-Gauge SX Staple

SX=7/32"
SL=5/16"

1/2" 3/4" 1" 1 1/4"
5/8" 7/8" 1 1/8" 1 3/8"
1 1/2"
(SX/SL150 ONLY)

FASTENERS: SX SERIES

BT35B-1, BT50B-1

Decorative Trim, Corner Block Nailer

Features:
- Extreme-duty, high cycle design (requires oil)
- Composite frame / Aluminum magazine
- Narrow nose for improved line of sight

Applications:
- Decorative molding, fine trim work

Tool Description:
BT35B-1
- Tool Weight: 2.4 lbs.
- Driving Pwr: 145 inch lbs. @ 100 psi
BT50B-1
- Tool Weight: 2.6 lbs.
- Driving Pwr: 165 inch lbs. @100 psi

18-Gauge Brad
BT50B

1 3/4"
1 3/8" 1 9/16" 2"
5/8" 1 3/8" 1 3/4"
3/4" 1 3/16" 1 3/8" 1 3/4" 2"
1" 1 1/4" 1 1/2"

BT35B

3/4" 1 3/16"
5/8" 1" 1 3/8"
5/8" 1" 1 1/4"
3/4" 1 3/16"

FASTENERS: BT SERIES

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

17

Fast, accurate, cost-effective manufactured housing relies on Bostitch® Industrial tools and fasteners.

Framing:

640S4

BRT130

863S4-1

538S214

Flooring/Underlayment:

863S4-1

S32SX-1

S32SL-1

Roofing:

450S2-1

438S2R-1

US056-1

Cabinet/Trim:

BT35B-1

BT50B-1

S32S

Sheathing/Siding:

IC60-1	538S4-1
N64084-1	650S4-1
N64099-1	650S5-1
N70CB-1	US056-1
N80CB-1	650S414Kit

Sheathing/Siding

Nationwide Expert SERVICE & REPAIR

SouthernCarlson®
Fastening. Packaging. Service.

SouthernCarlson® is an approved Service and Repair provider for

BOSTITCH® INDUSTRIAL

With over 140 locations in 34 States and Mexico, SouthernCarlson® has a network of service and repair technicians to keep your tools working at top performance. The entire SouthernCarlson® team is committed to ensuring your equipment runs seamlessly project after project.

Contact your sales professional for locations or visit www.SouthernCarlson.com

Roofing

Framing

Cabinet/Trim

Flooring

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

19

BRT130

Stick Timber Nailer

Features:
- Power-packed engine design drives nails up to 5-1/8"
- Oil-free, requires no lubrication
- Includes auxiliary handle for added comfort and control

Applications:
- Roof to ceiling connections
- Timber frames/log homes/pole barns

Tool Description:
- Nail Length: 5-1/8"
- Tool Weight: 15.4 lbs.
- Driving Pwr: 2075 inch lbs. @ 100 psi
- Magazine Capacity: 50

21° Plastic Collated Nails

Smooth   4"   4 1/2"   5 1/8"   6 1/4"

Available in: Plain, galvanized, stainless steel

FASTENERS: 21° PLASTIC COLLATED SERIES

IC60-1

Box Frame Nailer

Features:
- Uses wire collated nails
- Lightweight, compact design
- Durable cast aluminum frame and cap
- Quick-open composite canister survives falls
- Adjustable exhaust to direct air away from user
- Side wear guards and bumpers protect tool from damage
- Rubber grip for improved comfort and control
- 360 degree directional exhaust

Applications:
- Pallets assembly and repair
- Fence panel assembly
- Crate assembly Tool

Description:
- Tool Weight: 5.7 lbs.
- Driving Power: 445 inch lbs. @ 100 psi
- Magazine Capacity: 300 to 350 depending on nail size
- 1" to 2-1/4" (2d to 7d)

Screw   1 1/2" 1 3/4"

Ring   1"   1 1/4" 1 1/2" 1 3/4"   2"   2 1/4"

Smooth   1 1/4" 1 1/2" 1 3/4"   2"   2 1/4"

Available in: Plain, galvanized, stainless steel, aluminum

FASTENERS: AC, C, FC SERIES

N89C-1P, N80CB-1* *(for Canada only)*

Coil Framing Nailer

Features:
- Quick-open composite canister survives falls
- Drives wire collated nails .099"-.148"
- Durable aluminum housing
- Rubber comfort grip
- 360 degree directional exhaust

Applications:
- Framing, sheathing

Tool Description:
- Tool Weight: 8.1 lbs. / 8.4 lbs.
- Driving Power: 1050 inch lbs. / 880 inch lbs.
- Magazine Capacity: 225 to 300 depending on nail size

15° Coil Nails

Screw   3" 3 1/4"

Ring   1 3/4"   2"   2 1/4"   3" 3 1/4"

Smooth   1 1/2" 1 3/4"   2"   2 1/4"   3" 3 1/4"

Available in: Plain, galvanized, stainless steel

FASTENERS: AC, C, FC, FC Pallet Plus™ SERIES

450S2-1, 438S2R-1

Roofing Stapler

Features:
- Lightweight durable aluminum frame
- Anti-Jam™ magazine permits staples to exit nose without jamming
- Power control valve, adjusts power by 30%
- Long-lasting molded rubber comfort grip
- Reduced height for stapling in tight areas
- Rear exhaust directs exhaust away from user
- High-capacity, top load magazine decreases reload time
- Carbide inserts for long life (438S2R-1)
- 438S2R-1 has adjustable shingle gauge for fast layout

Applications:
450S2-1
- Shingles; roofing felt, house wrap, vapor barrier, butt joints, hurricane strapping

438S2R-1
- Composite shingle roofing
- House wrap, vapor barrier
- Sheathing

Tool Description:
450S2-1
- Tool Weight: 4.6 lbs.
- Driving Power: 230 inch lbs. @ 100 psi
- Magazine Capacity: 160
- 1/2 to 1-1/2 inch leg

438S2R-1
- Tool Weight: 4.7 lbs.
- Driving Power: 230 inch lbs. @ 100 psi
- Magazine Capacity: 160
- 1/2 to 2 inch leg

16-Gauge S2 Staple

1"

            21/32"   1"   1 1/2"
      1/2"   3/4"   1 1/4"

16-Gauge S4 Staple

1/2"

      1/2"   3/4"   1"   1 1/4"   1 1/2"
         5/8"   7/8"   1 1/8" 1 3/8"

FASTENERS: 16 S2 SERIES

BOSTITCH®

INDUSTRIAL

538S4-1, 538S5-1

Stapler, Truss Stapler
Features:
- Anti-Jam™ magazine permits staples to exit nose without jamming
- Long narrow nose for improved line of sight
- Adjustable trip for positive staple depth control
- Long magazine kit available
- 360 degree directional exhaust

Applications:
- Sheathing (1-1/2 inch leg)
- Truss Assembly

Two-In-One Truss Tool
- Stitches truss joints
- Attaches truss plates prior to roller press

Tool Description:
- Tool Weight: 4.7 lbs.
- Driving Power: 260 inch lbs. @ 100 psi
- Magazine Capacity: 160
- Long Magazine: 300 +
538S4-1: 16 Gauge 3/8" to 1-1/2" leg
538S5-1: 16/17 Gauge 1/2" to 2" leg

16 Gauge S4 Staple

1/2"   3/8" 3/4" 7/8" 1" 1 1/8" 1 1/4" 1 3/8" 1 1/2"

FASTENERS: 14, 16 S4 SERIES

650S4-1, 650S5-1

Sheathing, Siding Staplers
Features:
- Anti-Jam™ magazine permits staples to exit nose without jamming
- Increased power to countersink staples into hardwood
- Long-lasting molded rubber comfort grip
- Long narrow nose for improved line of sight in precise applications

Applications:
- Sheathing (1-1/2 inch leg)
- Truss Assembly

Tool Description:
- Tool Weight: 4.5 lbs.
- Driving Power: 340 inch lbs. @ 100 psi
- 16 Gauge 1" to 2" leg
- **650S4-1** Magazine Capacity: 160
- **650S5-1** Magazine Capacity: 171

16-Gauge S4 Staple

1/2"   1" 1 1/8" 1 1/4" 1 3/8" 1 1/2" 1 5/8" 1 3/4"   2"

16/17-Gauge S5 Staple

7/16"   1" 1 1/8" 1 1/4" 1 3/8" 1 1/2" 1 5/8" 1 3/4"   2"

FASTENERS: 16 S4, S5 SERIES

863S4-1

Flooring Stapler
Features:
- Anti-Jam™ magazine permits staples to exit nose without jamming
- Narrow nose for improved line of sight
- Adjustable trip for staple depth control

Applications:
- Flooring (plywood to frame)
- Sub-flooring

Tool Description:
- Tool Weight: 5.7 lbs.
- Driving Pwr: 570 inch lbs. @ 100 psi
- Magazine Capacity: 160
- Long Magazine: 260
- 1-1/2" to 2 inch leg

15-1/2-Gauge Staple

1/2"   1 1/2" 1 3/4" 2" 2 1/2"

15-Gauge Staple

1/2"   1 1/2" 1 3/4" 2" 2 1/4" 2 1/2"

FASTENERS: 15 S4 & 15 1/2 S4 SERIES

US056-1

Pneumatic PowerCrown™ Stapler/Box Frame Nailer
Features:
- Pneumatic operation for high production felt, insulation and other light-wire stapling applications
- Lightweight magnesium design
- Oil-free operation requires no regular maintenance and eliminates risk of oil stains
- Ultra-quiet rear exhaust
- Long-lasting molded rubber comfort grip

Applications:
- Roofing felt, house wrap vapor barrier application

Tool Description:
- Tool Weight: 2.1 lbs.
- Driving Power: 138 inch lbs. @ 100 psi
- Magazine Capacity: 84
- 1/4 to 9/16 inch leg

7/16"   1/4" 5/16" 3/8" 1/2" 9/16"

FASTENERS: STH5019 SERIES

S32SL-1, S32SX-1

Cabinet, Underlayment Staplers
Features:
• Extreme-duty, high cycle design (requires oil)
• Composite frame/aluminum magazine
• Narrow nose for accurate fastener placement

Applications:
• Cabinet work
• Underlayment:
(1/4" luan under vinyl flooring)

Tool Description:
S32SL-1
• Tool Weight: 2.5 lbs.
• Driving Power: 160 inch lbs. @ 100 psi
S32SX-1
• Tool Weight: 2.4 lbs.
• Driving Power: 160 inch lbs. @ 100 psi

18-Gauge SX Staple

SX=7/32"
SL=5/16"

1/2" 3/4" 1" 1 1/4"
5/8" 7/8" 1 1/8" 1 3/8"
1 1/2"
(SX/SL150 ONLY)

FASTENERS: SX SERIES

BT35B-1, BT50B-1

Decorative Molding, Fine Trim Nailer
• Extreme-duty, high cycle design (requires oil)
• Composite frame / Aluminum magazine
• Narrow nose for improved line of sight

Applications:
• Decorative molding, fine trim work
• Drawer; pinning French and other dovetail joints

Tool Description:
BT35B-1
• Tool Weight: 2.4 lbs.
• Driving Pwr: 145 inch lbs. @ 100 psi
BT50B-1
• Tool Weight: 2.6 lbs.
• Driving Pwr: 165 inch lbs. @ 100 psi

18-Gauge Brad
BT50B
1 3/4"
1 9/16"
1 3/8" 2"
5/8" 1 3/16" 1 3/8" 1 3/4"
3/4" 1" 1 1/4" 1 1/2 " 2"

BT35B
3/4" 1 3/16"
5/8" 1" 1 3/8"
5/8" 1" 1 1/4"
3/4" 1 3/16"

FASTENERS: BT SERIES

N70CB-1*

Heavy Duty Pallet Nailer
Features:
• Uses wire collated nails
• Angled coil design for high operator visibility
• Quick loading canister
• Better balance for operating ease
• 360 degree directional exhaust

Applications:
• Heavy duty pallet assembly

Tool Description:
• Tool Weight: 7.9 lbs.
• Driving Power: 738 inch lbs. @ 100 psi
• Magazine Capacity: 225 to 300 depending on nail size
• 1-1/2" to 2-3/4" (4d to 9d)

Screw
1 1/2" 1 3/4" 2" 2 3/16" 2 3/4"

Ring
1 1/2" 1 3/4" 2" 2 3/16" 2 3/4"

Smooth
1 1/2" 1 3/4" 2" 2 3/16" 2 3/4"

Available in: Plain, galvanized, stainless steel, aluminum**

**Aluminum nails require door conversion kit (Item#112670)

FASTENERS: AC, C, FC, FC Pallet Plus™ SERIES

N64084-1, N64099-1*

Pallet, Crate, Fence Nailer
Features:
• Uses wire collated nails
• Oversized canister opens completely for easy reloading
• Tool-free adjustable exhaust
• Oversized bore for driving
N64084-1
.084" Pallet Plus™ nails
N64099-1
.099" Pallet Plus™ and WB nails

Applications:
• Crate frames, medium duty pallet assembly and repair
• Fence panel assembly
• Picket assembly using aluminum nails

Tool Description:
• Tool Weight: 6.1 lbs.
• Driving Power: 560 inch lbs. @ 100 psi
• Magazine Capacity: 225 to 350 depending on nail size
• 1-1/4" to 2-1/2" (3d to 8d)

Screw
1 1/4" 1 1/2" 1 3/4" 2" 2 3/16" 2 1/2"

Ring
1 1/4" 1 1/2" 1 3/4" 2" 2 3/16" 2 1/2"

Available in: Plain, galvanized, stainless steel, aluminum**

FASTENERS: AC, C, ACP, FC SERIES

BOSTITCH®

INDUSTRIAL

There's no sleeping allowed on this job. Hard-working employees need tools that perform all day and night.

Box Frame Assembly:

IC60-1 Coil Nailer
438S4-1 Stapler
438S5-1 Stapler
BCAR-2S Stapler

Flange to Spring:

SC7 C-Ring Tool
SC7C C-Ring Tool
TR201 D-Ring Short Magazine
TR203 D-Ring Long Magazine
TR315 D-Ring Long Magazine

Fabric to Wood:

21671B 71 Series Stapler
21671B-LM Stapler
21680B 80 Series Stapler
21684BB

Fabric to Foam:

S32SL-OC Stapler

BCAR-2S Stapling foundation spring to flat

SC7 With manifold kit SCK014 securing pocketed coils w/C-Ring

438S4-1 Stapler connecting flat members

S32SL-OC Flange stapler applying flange to foam side

TR203 D-Ring tool connecting flange to innerspring

IC60-1

Box Frame Nailer

Features:
- Uses wire collated nails
- Lightweight, compact design
- Durable cast aluminum frame and cap
- Quick-open composite canister survives falls
- Adjustable exhaust to direct air away from user
- Side wear guards and bumpers protect tool from damage
- Rubber grip for improved comfort and control
- 360 degree directional exhaust

Applications:
- Pallets assembly and repair
- Fence panel assembly
- Crate assembly Tool

Description:
- Tool Weight: 5.7 lbs.
- Driving Power: 445 inch lbs. @ 100 psi
- Magazine Capacity: 300 to 350 depending on nail size
- 1" to 2-1/4" (2d to 7d)

Screw
Ring   1 1/2" 1 3/4"
Smooth   1"   1 1/4" 1 1/2" 1 3/4" 2" 2 1/4"
   1 1/4" 1 1/2" 1 3/4" 2" 2 1/4"

FASTENERS: AC, FC SERIES

438S4-1, 438S5-1

Box Frame Stapler
- Lightweight durable aluminum frame
- Jam-free magazine
- Power control valve, adjusts power by 30%
- Long-lasting molded rubber comfort grip
- Reduced height for stapling in tight areas
- Rear exhaust directs exhaust away from user and work surface
- High-capacity, top load magazine decreases reload time

Applications:
- Box frame/flat assembly

Tool Description:

438S4-1
- Tool Weight: 4.5 lbs.
- Driving Power: 230 inch lbs. @ 100 psi
- Magazine Capacity: 160
- 1/2" Crown, 3/4" to 1-1/2" leg

438S5-1
- Tool Weight: 4.5 lbs.
- Driving Power: 230 inch lbs. @ 100 psi
- Magazine Capacity: 160
- 7/16" Crown, 1-1/2" leg

16-Gauge S4 Staple
1/2"   3/8" 3/4" 7/8" 1" 1 1/8" 1 1/4" 1 3/8" 1 1/2"

16/17-Gauge S5 Staple
7/16"   1/2" 3/4" 7/8" 1 1/8" 1 1/4" 1 3/8" 1 1/2" 1 5/8"   2"

FASTENERS: 16 S4 SERIES

BCAR-25

Attaches Spring to Box Frame

Features:
- Pneumatic stapler for driving staples into hard-to-reach places such as bottoms of coil springs
- Available in single or double staple fire versions

Applications:
- Spring up (attaching springs to box frame)

Tool Description:
- Tool Weight: 7.4 lbs.
- Magazine Capacity: 100
- Staple Length: 3/4"

BSC31, BCS31P
16-Gauge Round
Crown Staple
3/8"
3/4"

FASTENERS: ROUND CROWN BOX SPRING SERIES

SC7, SC7C

Spring to Spring

Features:
- Balanced, lightweight, ergonomically designed
- Easy-to-load anti-back-up magazine
- Can be easily converted to right or left hand operation
- Manifold mounting kit available for zero gravity balancer suspension (vertical or horizontal): SCK014
- Zero gravity balancer: BAL5N

Applications:
- Pocket coil to pocket coil
- Pocket coil to borderwire
- Flange to innerspring/borderwire

Tool Description:
- Tool Weight: 2.8 lbs.
- Magazine Capacity: 125
- Jaw Length: 1-1/4"

RING15100P
3/4"

3/16"   5/16"

(Shown with balancer and manifold kit options.)

Available in: Basic brite steel, galvanized, aluminum, stainless steel

FASTENER: RING15100P

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

BOSTITCH

INDUSTRIAL

TR201, TR203, TR315

Flange to Innersprings

Features:
• TR201 Spring returned tool
• TR203 Spring returned tool long mag.
• TR315 High-speed air return, long mag.
• Magazine can be pivoted in 90° increments on TR315, and continuously on TR201 and TR203

Applications:
• Flange to inner spring

Tool Description:
• 15 ga. 3/4" D-Ring, 1/4" min. closure
• Short Magazine: 55 rings, 3.3 lbs.
• Long Magazine: 125 rings, 3.6 lbs.

15-Gauge D-Ring

3/4"   1/4"

Available in: Basic Steel, galvanized, stainless steel

FASTENER: 15-GAUGE D-RING

S32SL-OC

Fabric to Foam Stapler

Features:
• Designed for staple legs to flare outward, giving good holding power in soft material
• Adjustable flare from straight staple to moderate flare for good holding in thick, soft material to severe flare for shallow materials where staple cannot show on other side.

Applications:
• Fastening flange to foam encased innerspring
• Fabric to cardboard, foam
• Temporary pinning of fabric

Tool Description:
• Tool Weight: 2.8 lbs.
• Driving Power: 160 inch lbs. @ 100 psi
• Magazine Capacity: 100
• Staple Length: 1 inch typical (SL5031G)

SL Series: 5/16'' Crown

FASTENERS: SL SERIES

21671B, 21671B-LM, 21680B, 21680B-LN

Fabric to Wood Assembly

Features:
21671B:
• Very lightweight, rugged, all metal construction, quiet, low air consumption
21671B-LM:
• Same as BAT401 but with long magazine; cuts reloading time
21680B, 21680B-LN (long nose):
• Same as 21671B but fires 80 series staples

Applications:
• Securing fabric to wood frame
• Pre-upholstery spring up operation: attach cardboard, webbing, propex to frame
• Boat Seating with stainless steel staples
• 21697B Attaching double welt

Tool Description:
21671B
• Tool Weight: 1.81 lbs.
• Magazine Capacity: 196, 71 series staples
21671B-LM
• Tool Weight: 2.43 lbs.
• Magazine Capacity: 392, 71 series staples
21680B; 21680B-LN
• Tool Weight: 1.83 lbs.
• Magazine Capacity: 156, 80 series staples

71 Staple

3/8" 5/32" 1/4" 3/8" 1/2" 3/16" 5/16" 7/16" 9/16"

80 Staple

1/2" 1/4" 3/8" 1/2" 5/32" 5/16" 9/16"

FASTENERS: 71, 80 STAPLE SERIES

From decorative molding to fine trim work and even case backs, Bostitch® Industrial has the right pneumatic tool for the job.

Custom Millwork Calls for Premium Quality Tools and Fasteners.

Structural Assembly:

450S2-1 Stapler

538S4-1 Stapler

Trim Work:

S32SX-1 Stapler

S32SL-1 Stapler

BT35B-1 Nailer

BT50B-1 Nailer

Door/Window Frames:

650S4-1 Stapler

650S5-1 Stapler

651S5-1 Stapler

CF15-2 Corrugated Tool

CF15-2 Corrugated tool applying miter fastener to window frame

18-gauge brads applying trim

450S2-1 Stapler joining door jambs

S32SL-1, S32SX-1

Cabinet, Underlayment Stapler

Features:
• Extreme-duty, high cycle design (requires oil)
• Composite frame/aluminum magazine
• Narrow nose for improved line of sight

Applications:
• Cabinet work
• Underlayment:
  (1/4" luan under vinyl flooring)

Tool Description:
S32SL-1
• Tool Weight: 2.5 lbs.
• Driving Pwr: 160 inch lbs. @ 100 psi
S32SX-1
• Tool Weight: 2.4 lbs.
• Driving Pwr: 145 inch lbs. @ 100 psi

18-Gauge SX Staple

SX=7/32"
SL=5/16"

1/2" 3/4" 1" 1 1/4"
5/8" 7/8" 1 1/8" 1 3/8"
1 1/2"
(SX/SL150 ONLY)

FASTENERS: SX SERIES

BT35B-1, BT50B-1

Decorative Molding, Fine Trim Nailer

Features:
• Extreme-duty, high cycle design
  (requires oil)
• Composite frame / Aluminum magazine
• Narrow nose for improved line of sight

Applications:
• Decorative molding, fine trim work
• Drawer; pinning French and other
  dovetail joints

Tool Description:
BT35B-1
• Tool Weight: 2.4 lbs.
• Driving Pwr: 145 inch lbs. @ 100 psi
BT50B-1
• Tool Weight: 2.6 lbs.
• Driving Pwr: 165 inch lbs. @ 100 psi

18-Gauge Brad
BT50B

1 3/4"
1 3/8" 1 9/16" 2"
5/8" 1 3/16" 1 3/8" 1 3/4"
3/4" 1" 1 1/4" 1 1/2 " 2"

BT35B
3/4" 1 3/16"
5/8" 1" 1 3/8"
5/8" 1" 1 1/4"
3/4" 1 3/16"

FASTENERS: BT SERIES

538S4-1, 538S5-1

Medium Duty Structural Stapler

Features:
• Anti-Jam™ magazine permits staples to
  exit nose without jamming
• Long narrow nose for improved
  line of sight
• Adjustable trip for positive
  staple depth control
• Long magazine kit available
• 360 degree directional exhaust

Applications:
• Light and medium duty structural
  assembly

Tool Description:
• Tool Weight: 4.7 lbs.
• Driving Power: 280 inch lbs. @ 100 psi
• Magazine Capacity: 160
• 3/8" to 1-1/2" leg
538S4-1: 16 Gauge 3/8" to 1-1/2" leg
538S5-1: 16/17 Gauge 1/2" to 2" leg

1/2"
3/4" 1 1/8" 1 3/8"
3/8" 7/8" 1" 1 1/4" 1 1/2"

FASTENERS: 16 S4, S5 STAPLES

650S4-1, 650S5-1

Door, Window Frame Stapler

Features:
• Anti-Jam™ magazine permits staples
  to exit nose without jamming
• Increased power to countersink
  staples into hardwood
• Long-lasting molded rubber comfort grip
• Long narrow nose for improved line of
  sight in precise applications

Applications:
Door and window frames

Tool Description:
• Tool Weight: 4.5 lbs.
• Driving Power: 340 inch lbs. @ 100 psi
• 16 Gauge 1" to 2" leg
• **650S4-1** Magazine Capacity: 160
• **650S5-1** Magazine Capacity: 171

16-Gauge S4 Staple

1/2"
1" 1 1/4" 1 1/2" 1 3/4"
1 1/8" 1 3/8" 1 5/8" 2"

16/17-Gauge S5 Staple

7/16"
1" 1 1/4" 1 1/2" 1 3/4"
1 1/8" 1 3/8" 1 5/8" 2"

Available in: Coated

FASTENERS: 16 S4, S5 SERIES

450S2-1

Light Duty Structural Assembly Stapler

Features:
- Lightweight durable aluminum frame
- Anti-Jam™ magazine permits staples to exit nose without jamming
- Power control valve, adjusts power by 30%
- Long-lasting molded rubber comfort grip
- Reduced height for stapling in tight areas
- Rear exhaust directs exhaust away from user and work surface
- High capacity, top-load magazine decreases reload time

Applications:
- Light duty structural assembly

Tool Description:
- Tool Weight: 4.6 lbs.
- Driving Power: 230 inch lbs. @ 100 psi
- Magazine Capacity: 160
- 1/2" to 2" leg

16-Gauge S2 Staple

1"

1/2"   3/4"   1"   1 1/4"   1 1/2" 1 3/4"   2"

Available in: Coated

FASTENERS: 16 S4, S5 SERIES

CF15-2

Door, Cabinet Mitre Nailer

Features:
- Lightweight durable frame
- Powerful to provide full penetration of stringers
- 360 degree directional exhaust

Applications:
- Joining door stiles, cabinet face frames
- Stile assembly, door and window fabrication

Tool Description:
- Tool Weight: 6.58 lbs.
- Magazine Capacity: 128

Corrugated

1"

3/8" 09
1/2" 12
5/8" 15

Available in: Aluminum

FASTENERS: CORRUGATED/MITRE SERIES

IC60-1

Box Frame Nailer

Features:
- Uses wire collated nails
- Lightweight, compact design
- Durable cast aluminum frame and cap
- Quick-open composite canister survives falls
- Side wear guards and bumpers protect tool from damage
- Rubber grip for improved comfort and control
- 360 degree directional exhaust

Applications:
- Structural Assembly

Description:
- Tool Weight: 5.7 lbs.
- Driving Power: 445 inch lbs. @ 100 psi
- Magazine Capacity: 300 to 350 depending on nail size
- 1" to 2-1/4" (2d to 7d)

Screw   1 1/2" 1 3/4"

Ring   1"   1 1/4" 1 1/2" 1 3/4"   2"   2 1/4"

Smooth   1 1/4" 1 1/2" 1 3/4"   2"   2 1/4"

FASTENERS: A, AC, FC SERIES

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

CARTON CLOSURE

Companies thrive on getting the job in and then out. Bostitch® Industrial has an extensive line of carton closure tools and fasteners to help get the boxes out the door.

P3-IND Industrial Plier	ESD-450S2P Plier Tool	02245 B8 Stapling Plier	BTFP12182 Jumbo Stapler
P6C-6 Stapling Plier	P51-10B Stapler	DS-3219 Stapler	F84-138 Corrugated Box Post Machine
P6C-8 Stapling Plier	P51-5B Stapler	DS-3522 Stapler	FC96EC Corrugated Box Post Machine
P6C-8P Stapling Plier	D62ADC Top Closure	BTFP12180 Stapler	
JB600 Stapler	D62ADCSB Top Closure	BTFP12181 Stapler	

FC96EC Bottom closer used to clinch
carton bottoms

P51-10B Fastening carton side

D62ADCSB With pointed anvil piercing
corrugated to seal container from outside

BAG CLOSURE

From poultry to automotive parts, if it comes packaged in a bag, we have the closure to make sure it stays there.

P6C-8P Stapling Plier	SC7 C-Ring Tool	SC761 C-Ring Tool	TR201 D-Ring Closure
P7 C-Ring Hand Plier	SC7C C-Ring Tool	SC742 C-Ring Tool	TR203 D-Ring Closure
HFP9 C-Ring Hand Plier	SC7E Extended Nose C-Ring Tool	SC743 C-Ring Tool	TR315 D-Ring Closure
SC50HP C-Ring Hand Plier	SC760 C-Ring Tool	SC50T Gabion C-Ring Tool	

SC7 Equipped with MTCKA7 touch trip

Low cost P7 being used to seal potato bag

**Bait bag secured with 15-gauge
stainless steel C-ring**

**Oil absorption socks can be secured
with 11, 15 or 16-gauge blunt C-rings**

P6C-6, P6C-8, P6C-8P, JB600

Box Closing, Dry Cleaning

Features:

P6C-8:
• Bearing system allows an easy squeeze action across entire operating sequence creating a quicker, tighter clinch with less strain
• Available in P-Pointed blade version (P6C-8P) to penetrate cartons to clinch staple
• Coated top-load magazine permits faster, smoother staple loading

P6C-6:
• Same as P6C-8 but with lighter wire staple

JB600:
• Air drive version of P6C-8 allows continuous use without stress
• Top loading magazine

Applications:
P6C-6:
• Fastening Header cards to plastic bags, etc.
• Assembling small cardboard boxes

Tool Description:

P6C-6
• Tool Weight: 1 lbs.
• Magazine Capacity: 158
• Throat Size: ~3/8" x 2-1/2"

P6C-8
• Tool Weight: 1 lbs.
• Magazine Capacity: 85
• Throat Size: ~3/8" x 2-1/2"
• Pneumatic assembly available

JB600
• Tool Weight: 2.4 lbs.
• Magazine Capacity: 85
• Throat Size: ~3/8" x 2-1/2"

Applications:
P6C-8:
• Header cards to plastic bags
• Box closing
• Corrugated assembly
• Dry cleaning

JB600:
• Lightweight manufacturing and packaging

Bostitch® Light Wire PowerCrown™ Staples STCR2619 Series

7/16" 1/4" 3/8" 5/16" For: P6C-6

Bostitch® PowerCrown™ Staples STH5019 Series

7/16" 1/4" 3/8" 9/16" 5/16" 1/2" For: P6C-8 P6C-8P

FASTENERS: STCR2619 & STH5019 SERIES

02245

Dry Cleaner and Florist Industry

Features:
• Rugged design for heavy use
• Top-load magazine

Applications:
• Dry cleaner and Florist industry

Tool Description:
• Tool Weight: 0.75 lbs.

7/16"
Bostitch® PowerCrown™ Staples

7/16" 1/4" 3/8"

FASTENERS: STH2115 SERIES

P7

Plastic, Cloth, or Mesh Bag Closure

Features:
• Spring-loaded magazine feed
Also see RINGER9/16 on page 37

Applications:
• Closes off the neck of a twisted plastic, cloth or mesh bag

Tool Description:
• Tool Weight: 0.8 lbs.

11/16" 9/32"

Available in: Galvanized, stainless steel

FASTENERS: SPENAX™ RINGS SERIES

P3-IND

Tagging, Wrapping, Shipping

Features:
• Fine wire lightweight staple
• Top load magazine with cover/pusher that stays with the tool
• Rugged design for heavy use with movable, breathing core to prevent jamming
• Pass-by clinch so one staple will fasten various thickness applications

Applications:
• Dry cleaner garment tagging, drugstore bag closure, price tag to garment, etc.
• Flower wrapping
• Badges and ribbons
• Shipping room packaging

Tool Description:
• Tool Weight: 0.5 lbs.
• Magazine Capacity: 208

SP191/4

3/8" 1/4"

FASTENERS: 3/8" CROWN STAPLE SERIES

HFP9

Large Bag Closure
Features:
• 1-3/16 inch opening
• Spring-loaded magazine feed allows collated hog rings to feed directly into jaws
• Magazine pivots so it won't interfere with bag body

Applications:
• Wide opening for thick material or large bag closure

Tool Description:
• Tool Weight: 1.0 lbs.

RING09AL25

1 3/16"   7/16"

Available in: Aluminum

FASTENERS: SPENAX™ RINGS SERIES

TR201, TR203, TR315

Small Bag Closure
Features:
• TR201 Spring returned tool
• TR203 Spring returned tool long mag.
• TR315 High-speed air return, long mag.
• Magazine can be pivoted in 90° increments on TR315, and continuously on TR201 and TR203

Applications:
• Small bag closure

Tool Description:
• 15 ga. 3/4" D-Ring, 1/4" min. closure
• Short Magazine: 55 rings, 3.3 lbs.
• Long Magazine: 125 rings, 3.6 lbs.

15-Gauge D-Ring

3/4"   1/4"

Available in: Basic Steel, galvanized, stainless steel

FASTENER: 15-GAUGE D-RING

SC760, SC761, SC743, SC7, SC7C, SC73462*

Small to Medium Bag Closure
Features:
• SC743 set up with a zero balancer and manifold kit on a production line is ideal for applications where the bag is too heavy to easily lift
• Also see SC73462 for 1/16" bag closure

Applications:
SC760, SC761
• Small/medium bag closure
SC743
• Medium/large bag closure: concrete/powder, etc. bag liner closure

Tool Description:
SC760, SC761
• Tool Weight: 2.8 lbs.
• Magazine Capacity: 145
SC743, SC7, SC7C
• Tool Weight: 2.8 lbs.
• Magazine Capacity: 125 rings

w/SC760   w/SC761

1/2"   1/8"   3/16"   15-Gauge
                                  3/4"

16-Gauge

3/16"   5/16"
3/4"   w/SC743   3/16"   w/ SC7
                              w/ SC7C

Available in: Galvanized, aluminum, stainless steel

FASTENERS: SPENAX™ RINGS SERIES

SC50T

Very Large Bag Closure
Features:
• Air driven
• Large 1-1/2" opening
• MTCKA3 touch trip, bag guide kit
• MTCKA50 foot valve, bag guide kit
  See SC50HP for low-volume, hand plier version

Applications:
• Very Large bag closure

Tool Description:
• Tool Weight: 14.3 lbs.
• Magazine Capacity: 125 rings

9/16''

1 1/2''

Available in: Galvanized, aluminum, stainless steel

FASTENERS: SPENAX™ RINGS SERIES

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.   *Special Order

D62ADC

Top Corrugated Carton Closure

Features:
- Drives the staple into corrugate at the same time two clincher arms penetrate on either side of staple legs, clinching staple
- Tool is rested on the carton, trigger is squeezed for a strong carton, fastening from the outside
- Full cycle action for maximum speed, quick release to prevent jams and an adjustment for tightness and depth of clinch

Applications:
- Top closing virtually all types of corrugated containers where speed and maneuverability are a must
- Ideal for replacing or enhancing glue systems where added reliability and security are a must

Tool Description:
- Tool Weight: 5.56 lbs.
- Coil of 1000/load

SWC7437
1-3/8"
5/8"
1/2" 3/4"

FASTENERS: SWC7437 1-1/8" WIDE CROWN COIL PACKAGING STAPLE

DS-3219, DS-3522

Corrugated Carton Closure
- Easy load magazine designed for high production environments
- Fast Staple depth adjustment designed for ease of use
- Full cycle actuation designed for maximum speed
- Rubber grip for added comfort

Applications:
- Carton closing

Tool Description:
- Tool Weight: 7Lbs
DS-3219:
- C-Series 1-1/4"
- Adjusts to use 5/8" and 3/4" length staples (B58C and B34C)
DS-3522:
- A-Series 1-3/8"
- Drives 5/8", 3/4", and 7/8" staple items 7437 Series and 9040 "A" crown staples to cover most corrugated box lid stapling applications.

1-1/4" B58C 5/8"
1-1/4" B34C 3/4"

1-3/8" SW9040 5/8" 7/8" 3/4"
1-3/8" SW7437 3/4" 5/8"

FASTENERS: 7237 SERIES, 9040 "A" CROWN STAPLES

BTFP12180, BTFP12181

Manual Corrugated Carton Closure
- Easy load magazine designed for high production environments
- Fast Staple depth adjustment designed for ease of use
- Full cycle actuation designed for maximum speed
- Rubber grip for added comfort

Applications:
- Low volume carton closing

Tool Description:
- Tool Weight: 7Lbs
- Magazine capacity: 100 staples
BTFP12180:
- C-Series 1-1/4"
- Adjusts to use 5/8" and 3/4" length staples (B58C and B34C)
BTFP12181:
- A-Series-1 3/8"
- Drives 5/8", 3/4", and 7/8" staple items 7437 Series and 9040 "A" crown staples to cover most corrugated box lid stapling applications.

1-1/4" B58C 5/8"
1-1/4" B34C 3/4"

1-3/8" SW7437 3/4" 5/8"
1-3/8" SW9040 5/8" 7/8" 3/4"

FASTENERS: 7237 SERIES, 9040 "A" CROWN STAPLES

BTFP12182

JUMBO Triple Wall Corrugated Carton Closer
- Adjustable clinchers for different thicknesses of cardboard and staple clinch tightness
- Blind fastens double and triple wall corrugated boxes
- Full cycle actuation designed for maximum speed
- Rubber grip for added end user comfort
- Drives staples up to 1-1/2" length

Applications:
- Double and triple wall carton closing

Tool Description:
- Magazine capacity: 100 staples
- Weight 13.2 Lbs
- 1-1/4" Crown
- Uses SW9060 Series box staples

1-1/4" SW9060 1-1/2"

FASTENERS: SW9060 SERIES

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

33

450S2-1

Light Duty Structural Assembly Stapler

Features:
- Lightweight durable aluminum frame
- Anti-Jam™ magazine permits staples to exit nose without jamming
- Power control valve, adjusts power by 30%
- Reduced height for stapling in tight areas
- Long-lasting molded rubber comfort grip
- Rear exhaust directs exhaust away from user and work surface
- High capacity, top-load magazine decreases reload time

Applications:
- Attaching corrugate to wood frame
- Wooden support and crate assembly

Tool Description:
- Tool Weight: 4.6 lbs.
- Driving Power: 230 inch lbs. @ 100 psi
- Magazine Capacity: 160
- 1/2" to 2" leg

16-Gauge S2 Staple

1"

1/2" 3/4" 1" 1 1/4" 1 1/2" 1 3/4" 2"

Available in: Coated

FASTENERS: 16 S2, S5 SERIES

ESD-450S2P

6 Layer Clinching

Features:
- Pliers compresses corrugate drives and clinches staple with single trigger actuation
- Innovative power control valve, easily adjust power by 30%

Applications:
- Applications requiring clinching of more than 6 layers of cardboard such as end caps or spacers

Tool Description:
- Tool Weight: 8.5 lbs.
- Magazine Capacity: 160 staples
- Throat 8" deep x 1-1/2" high
- Walking stick option available
- 1/2" to 2" leg

16-Gauge S2 Staple

1"

1/2" 3/4" 1" 1 1/4" 1 1/2" 1 3/4" 2"

FASTENERS: 16 S2 SERIES

P51-10B, P51-5B

Carton Closing

Features:
- Powerful shuttle blade provides pre-compression squeezes material prior and during the driving and clinching operation, giving a strong tight closure without breaking the corrugated surface
- 6 inch by 1 inch high throat allows flexibility of staple placement and limits interference from obstacles such as box flanges

Applications:
- Fastening corrugated containers, vegetable tray boxes, end caps, pallet boxes, container inserts, die cut inserts, etc.
- Stapling of fabric

Tool Description:
- Tool Weight: 4.5 lbs.
- P51-10B Magazine Capacity: 102
- P51-5B Magazine Capacity: 168
- Penetrates and securely fastens up to two thicknesses of double wall AB flute 500 lb. test board or four thicknesses of single wall C flute 275 lb. test board (for more layers see ESD-450S2P)
- Kits available: P51K1 kit with foot valve, remote trigger valve and clincher; P51181 remote trigger valve; P50152A mattress clincher

For P51-5B

SB 5019   .050

1/2"

1/4" 1/2"

3/8" 5/8"

For P51-10B

SB 103020   .103

1/2"

1/2"

3/8" 5/8"

FASTENERS: SB5019 AND SB103020 SERIES

D62ADCSB*

Hand-Free Closure

Features:
- Same as D61ADC but bench mounted with large 4000 staple coil
- Carton contact activated trip allows operator to use both hands to maneuver carton for side strike stapling
- Ideal for replacing or enhancing glue systems where added reliability and security are a must

Applications:
- Hand-free small to medium box closure
- Ideal for overlap cartons and five-panel folders
- Ideal for replacing or enhancing glue systems where added reliability and security are a must

Tool Description:
- Tool Weight: 28 lbs.
- Coil of 4000

SWC7437

1-3/8"

5/8" 7/8"
3/4"

FASTENERS: 1-3/8" WIDE CROWN COIL SERIES

F84-138

Low-Volume Carton Closing

Features:
- 16-1/2" throat depth and anvil post height of 36 inches allow most cartons to be stapled in one motion without reversing carton direction
- Will handle standard and heavy wire wide crown staples
- Anti-Jam™ interlock to prevent accidental jams, simple design for long life

Applications:
- Low-volume carton bottom closing

Tool Description:
- Tool Weight: 84 lbs.
- Magazine Capacity: 240 staples

SW9040 — 1-3/8" — 5/8" 7/8" 3/4"

SW7437 — 1-3/8" — 5/8" 3/4"

FASTENERS: 1-3/8" WIDE CROWN STICK STAPLE SERIES

FC96EC

High-Volume Carton Closing

Features:
- 24-inch throat and 40-inch anvil post height allow most cartons to be stapled in one motion without reversing carton direction
- 24-inch arm model (FC96ECARM) with clinching anvil coming off vertical post available for closing sidewalls, tray boxes and package fillers

Applications:
- High volume carton bottom closing

- Tool Weight: 230 lbs.
- Coil of 4000/load
- 180 staples/min speed
- Motor 1/4 hp 1725 rpm, 115/230 VAC, 60 cycle, capacitive start
- Welded steel construction

SWC7437 — 1-3/8" — 5/8" 1/2" 3/4"

FASTENERS: 1-3/8" WIDE CROWN COIL PACKAGING STAPLE SERIES

BOSTITCH

INDUSTRIAL

Every Specialty Fastening Job is different, but we can evaluate a sample of your application and recommend the Bostitch® Industrial fastener that best fits your needs.

1

Automotive seating cover secured to frame with a 15-gauge C-ring. Back assembly fastened with clinch clip.

2

Automotive control cables, brackets secured with C-rings.

3

Pre-cast concrete welded wire form secured with 11-gauge C-rings.

4

Large diameter rope loop secured with 11-gauge C-rings.

5

Bungee cord end can be secured with 11, 14, 15 or 16-gauge C-ring.

6

Coated and non-coated wire secured with a SC73462 tool and a 16-gauge aluminum C-ring.

7

Cargo netting to rope can be connected with 11, 14, 15 or 16-gauge C-ring.

8

Garland can be secured with an 11 or 15-gauge aluminum C-ring

9

P7 tightening up a burlap root ball.

10

P7 permanently attaching a label to a potted container.

11

Rubber tree support secured with two 11-gauge C-rings.

12

SC743 tightening a root ball with a 16-gauge C-ring.

13

SC742 short magazine tool attaching pot head to cage frame

14

Bait bag secured with 15-gauge stainless steel C-ring

15

Cage grid secured with a blunt 15-gauge C-ring.

16

Machine mounted 750S4 Stapler equipped with remote TVA-4 trigger valves.

17

Oil absorption socks can be secured with 11, 14, 15 or 16-gauge blunt C-rings.

18

Heat and sound insulation stitched with 16-gauge stainless steel C-rings.

19

HFP9 Attaching tensioning wire to chain-link fence with 9 gauge aluminum hog rings

20

Barbed tape loop formed with 11-gauge C-Ring

AUTOMOTIVE

We provide a wide range of tools for auto seat, upholstery and control cable applications.

SC7, SC7C

SC7E **SC77XE**

216 Series

A. Ring Tools for automotive upholstery small control cables
(See page 33 for tool details / See photo #1 & 2 on page 35)

SC7: Standard C-ring tool for most seat applications

SC7C: For applications where tight closure of ring is needed

SC7E: Extended nose for hard-to-reach applications

SC77XE: Maximum nose length for deep trenches and bolsters

B. 216 Series
(See page 14 for tool details / See photo on page 13)

21671B: Very lightweight, rugged, all metal construction, quiet, low air consumption.

21671B-LM: Same as 21671B but with long magazine; cuts reloading time.

21671B-LN: Same as 21671B but with extended nose for greater visibility and access to hard-to-reach areas, long nose also helps prevent scarring and scratching of wood.

21671B-A: 2-function trigger: light squeeze for single fire mode; full squeeze for auto fire mode. Auto fire rate can be adjusted from 0 to 1600 staples/minute. Same hand that activates trigger also opens magazine allowing for new staple insertion with the free hand.

21671B-ALM: Same as 21671B-A but w/long magazine (392 Staples) 21680B, 21680B-LN (long nose): Same as 21671B but fires 80 series staples.

*For **Ring Selection Guide** See Pages 46 & 47*

CONCRETE PIPE AND PRE-CAST CONCRETE WELDED WIRE REINFORCEMENT

Clinch clip and steel rings provide a faster low-cost alternative to welding of rolled wire mesh pipe reinforcement grids as well as forming of other NON-STRUCTURAL pre-cast pieces prior to casting.

SC50T

SC50HP

Ring Tools for Welded Wire Reinforcement

A. SC50T: Pneumatic large ring tool used with 11-gauge rings to join larger diameter reinforcement wire
(See page 33 for tool details / see application photo #3 on page 35)

B. SC50HP: Hand plier to join reinforcement wire for low-volume use and repairs (RING11AL40, RING11RG40 only). Tool Weight: 9.7 lbs., Magazine Capacity: 42 rings

*For **Ring Selection Guide** See Pages 46 & 47*

CAGE & TRAP ASSEMBLY

We can provide wire joining and hinge solutions for most cage and trap applications.

A

SC742

B

RINGR9/16

C

IC60-1

A. Ring Tools for Trap / Pot Heads (Netting) to Frame

SC742 C-Ring: Tool has short magazine for easy movement inside confined areas
   (See page 12 / See application photo #13 on page 35)

SC742: 16 gauge 3/16" ring closure for 3/4"x 3/4" wide grid

SC760: 16 gauge 1/8" ring closure for 1/2" x 1/2"wide grid

B. RINGER9/16: For repair of traps, pot heads and escape vents

C. IC60-1: Coil Nailer for applying stainless steel nails to pot runners
   (See page 24 for tool details)

*For **Ring Selection Guide** See Pages 46 & 47*

FENCING

A

HFP9

B

SC50T

C

SC50HP

A. HFP9: Fencing plier is used to attach tension wire to bottom of fences, connect fence 'butt ends' attach signs, etc.
   (See page 34 for tool details / See application photo #19 on page 35)

B. SC50T: For securing coiled razor wire using C-rings
   (See page 33 for tool details / See application photo #20 on page 35)

C. SC50HP: Hand Plier for low-volume and field connections of razor wire loops (RING11AL40, RING11RG40 only). Tool Weight: 9.7 lbs., Magazine Capacity: 42 rings

*For **Ring Selection Guide** See Pages 46 & 47*

NURSERY / LANDSCAPING / EROSION CONTROL

A

P7

B

SC7C

A. P7: Low cost method for tightening burlap on root ball after tie-up. Provides secure method to permanently affix tags to potted plants.
(See page 34 for tool details / see application photo #9 on page 35)

B. SC7C: High-volume method for tightening burlap after tie-up; also used for silt fence applications.
(See page 33 for tool details / see application photo #12 on page 35)

C. RINGER9/16: For pot tagging and arrangements.

D. SC50HP: Used for loop-forming on rubber tree supports. *(See photo #11 on page 35)* Also useful for large wreaths, garland to wire fastening *(See photo #8 on page 35)*, and irrigation strain wire to hose. Tool Weight: 9.7 lbs., Magazine Capacity: 42 Rings

E. SC50HP: Ideal for erosion control netting

C

RINGER9/16

D

SC50HP

D

SC50T

*For **Ring Selection Guide** See Pages 46 & 47*

LOOP FORMING: Rope, Bungee, Wire / Netting

SC7 Series

SC50HP

Our clips and hog rings make excellent quick knot replacements for low and medium force applications. We encourage sending in samples for factory recommendations.
(See page 33 for details / See photo # 4, 5, 6, 7, 11 on page 35)

SC50T

SC50T - Ideal for Erosion Control Netting

HEAT AND SOUND INSULATION

SC742, SC743, SC761

The SC7, SC743 and SC761, coupled with our sharp points and 16-gauge Stainless Steel C Ring, make short, efficient work out of stitching together tough insulation fabrics.
(See page 33 for details / See photo # 4, 5, 6, 7, 11 on page 35)

*For **Ring Selection Guide** See Pages 46 & 47*

NAIL - Tool Selection Guide

Nail Collation: Nails are collated using wire weld, plastic, tape or glue and are available in coil or stick format.

Nail Shank: There are three types of nail shanks. A **Smooth** shank has good withdrawal capacity, a **Ring** shank has increased withdrawal capacity in soft woods and a **Spiral** shank increases withdrawal capacity and driving power in hardwoods.

Nail Point: There are four basic point styles from which to choose:
(DP) Diamond Point: General purpose, best holding power
(BDP, BD) Blunt Diamond Point: Effective at reducing wood splitting and increasing driving power in hardwood applications
(CP) Chisel Point: The preferred point for trim applications
(BCP, BC) Blunt Chisel Point: Effective at reducing wood splitting in hardwood applications

DP
BDP
CP
BCP

Smooth   Ring   Spiral

Pack Quantity = Fasteners Per Pack   **Case Quantity =** Packs Per Case   **Skid Quantity =** Cases Per Skid

Item Number	Reference #	Description	Type	Pack	Case	Skid	Application Tools
AC SERIES - ANGLED COIL NAILS							
AC10DR	159513	3in X .120 Ring BDP	Round Head Coil Wire	4.5	0	42	N80CB-1, N89C-1P, N100C-1, N400C-1
AC12DS	685539	3-1/4in X .120 Screw BDP	Round Head Coil Wire	4.5	0	36	N80CB-1, N89C-1P, N100C-1, N400C-1
AC12DS131BDP	196174	3-1/4in X .131 Screw BDP	Round Head Coil Wire	4.5	0	36	N80CB-1, N89C-1P, N100C-1, N400C-1
AC2DR080BDP	290160	1in X .080 Ring BDP	Round Head Coil Wire	14	0	42	IC60-1, N64084-1
AC3D080BDP	196198	1-1/4in X .080 Sm BDP	Round Head Coil Wire	14	0	48	IC60-1, N64084-1
AC3DR080BDP	498785	1-1/4in X .080 Ring BDP	Round Head Coil Wire	14	0	48	IC60-1, N64084-1
AC4D080BDP	473270	1-1/2in X .080 Sm BDP	Round Head Coil Wire	14	0	30	IC60-1, N64084-1
AC4D113BDP	196204	1-1/2in X .131 Sm BDP	Round Head Coil Wire	7.5	0	40	N70CB-1, N80CB-1, N89C-1P
AC4DR080BDP	313729	1-1/2in X .080 Ring BDP	Round Head Coil Wire	14	0	30	IC60-1, N64084-1, N64099-1
AC4DSP113-LH	196211	1-1/2in X .113 Spiral T	Round Head Coil Wire	12	0	30	N70CB-1, N80CB-1
AC5D080BDP	901509	1-3/4in X .080 Sm BDP	Round Head Coil Wire	14	0	30	IC60-1, N64084-1
AC5DR080BDP	467265	1-3/4in X .080 Ring BDP	Round Head Coil Wire	14	0	30	IC60-1, N64084-1
AC6D090BDP	196228	2in X .090 Sm BDP	Round Head Coil Wire	12	0	30	IC60-1, N64084-1
AC6DR090BDP	468160	2in X .090 Ring BDP	Round Head Coil Wire	12	0	30	IC60-1, N64084-1
AC6DSP083MG	196235	2in X .083 Spiral NL MECG DP	Round Head Coil Wire	14	0	30	IC60-1, N64084-1
AC8DRBDP	473300	2-1/2in X .113 Ring BDP	Round Head Coil Wire	5	0	42	N70CB-1, N80C, N100C-1
AC8DSP09972	196273	2-1/2in X .099 Spiral BDP	Round Head Coil Wire	7.2	0	36	N70CB-1, N80C, N100C-1
ACL SERIES - ANGLED COIL NAILS							
ACL16D162BDP	744090	3-1/2in X .162 LG Coil SM BDP	Round Head Coil Wire	2.25	0	48	Auto Mach Mnted N400C-1, N100C-1
ACL3DR080BDP	196280	1-1/4in X .080 Ring BDP	Round Head Coil Wire	14	0	30	IC60-1
ACL3DWG99BD-PP	196297	1-1/4in X .099 Wedgegrip BDP	Round Head Coil Wire	12	0	36	Auto Mach Mnted N70CBPAL, N80CBPAL, & N89C-1P (Lg nail application)
ACL4DRBDG	196310	1-1/2in X .090 Ring BDP	Round Head Coil Wire	11.4	0	24	N64084-1, IC60-1
ACL5DR090BDSS	196327	1-3/4in X .090 Ring SS	Round Head Coil Wire	12	0	0	IC60-1, N70CB-PAL
ACL5DS099BCPRM	196334	1-3/4in X .099 LG Coil Screw BCP	Round Head Coil Wire	9	0	30	
ACL5DS099BDPRM	273410	1-3/4in X .099 Lg Blunt Dp Screw	Round Head Coil Wire	9	0	0	
ACL6D099BD-PP	473942	2in X .099 LG Coil BDP	Round Head Coil Wire	9	0	24	
ACL6DS099BCPRM	196341	2in X .099 LG Coil Screw BCP	Round Head Coil Wire	9	0	30	
ACL6DS099BDPRM	159520	2in X .099 LG Coil Screw BDP	Round Head Coil Wire	9	0	45	
ACL7DS099BCPRM	196358	2-1/4in X .099 Screw BCP	Round Head Coil Wire	9	0	30	Auto Machine Mounted N70CBPAL, Auto Machine Mounted N80CBPAL, & N89C-1P (for Large nail application)
ACL7DS099BD-PP	577565	2-1/4in X .099 LG Coil Screw BDP	Round Head Coil Wire	3	0	24	
ACL7DS099BDP	196365	2-1/4in X .099 Screw BDP	Round Head Coil Wire	9	0	24	
ACL7DS099BDPRM	167525	2-1/4in X .099 Screw BDP	Round Head Coil Wire	9	36	30	
ACL8DS099BD-PP	196389	2-1/2in X .099 LG Coil Screw BDP	Round Head Coil Wire	9	0	24	
ACL8DS099BDP	196372	2-1/2in X .099 Screw BDP	Round Head Coil Wire	9	0	24	
ACL8DS099BDPRM	196396	2-1/2in X .099 Screw BDP	Round Head Coil Wire	9	0	30	
ACL8DSP099	196402	2-1/2in X .099 Spiral	Round Head Coil Wire	1	0	24	

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

Item Number	Reference #	Description	Type	Pack	Case	Skid	Application Tools
C SERIES - 15° COIL FRAMING NAILS							
C20P131D	541828	4in X .131 Sm DP	Round Head Coil Wire	2.7	0	32	N100C-1, N400C-1
C20P131DG	380953	4in X .131 Sm DP Galv	Round Head Coil Wire	2.7	0	32	
C20S120D	159537	4in X .120 Screw DP	Round Head Coil Wire	2.7	0	32	
FC SERIES COIL NAILS - PALLET PLUS							
FC3DWG099BD-PP	428341	1-1/4in X .099 Wedgegrip BDP	Round Head Coil Wire-Pallet	9	0	36	N64099-1 (Deck Mat Nail), N70CB-1
FC5DS099BD-PP	196556	1-3/4in X .099 Screw BDP	Round Head Coil Wire-Pallet	12	0	42	N64099-1, N70CB-1, N80CB-1
FC6DS084BD-PP	380762	2in X .084 Screw BDP	Round Head Coil Wire-Pallet	12	0	64	IC60-1, N64084-1
FC6DS099BD-PP	456044	2in X .099 Screw BDP	Round Head Coil Wire-Pallet	9	0	48	N64099-1, N70CB-1, N80CB-1
FC7DS084BD-PP	380878	2-1/4in X .084 Screw BCP	Round Head Coil Wire-Pallet	12	0	24	IC60-1, N64084-1
FC7DS099BD-PP	456051	2-1/4in X .099 Screw BDP	Round Head Coil Wire-Pallet	10.8	0	42	N64099-1, N70CB-1, N80CB-1
FC8DS099BD-PP	505308	2-1/2in X .099 Screw BDP	Round Head Coil Wire-Pallet	6	0	54	N64099-1, N70CB-1, N80CB-1
FC SERIES - COIL NAILS							
FC10DR135BD-PH	196495	3in X .135 Ring BDP	Round Head Coil Wire-Pallet	4.5	0	30	N100C-1, N400C-1
FC10DS	869847	3in X .120 Screw DP	Round Head Coil Wire-Pallet	5.4	0	36	N80CB-1, N89C-1P, N100C-1, N400C-1
FC10DS113BD	196501	3in X .113 Screw BDP	Round Head Coil Wire-Pallet	6	0	36	N80CB-1, N89C-1P, N100C-1, N400C-1
FC16DS131	456013	3-1/2in X .131 Screw DP	Round Head Coil Wire-Pallet	2.7	0	50	N89C-1P, N100C-1, N400C-1
FC20DS131	181729	4in X .131 Screw DP	Round Head Coil Wire-Pallet	2.7	0	45	N100C-1, N400C-1
FC4D080-OD	196518	1-1/2in X .080 Sm Offset DP	Round Head Coil Wire-Pallet	16.8	0	36	N58C, IC60-1, N64084-1
FC4DS080BD	159575	1-1/2in X .080 Screw BDP	Round Head Coil Wire-Pallet	16.8	0	36	N58C, IC60-1, N64084-1
FC5DS080BD	196525	1-3/4in X .080 Screw BDP	Round Head Coil Wire-Pallet	16.8	0	30	IC60-1, N64084-1
FC5DS084BDPP16	196532	1-3/4in X .084 Screw BDP	Round Head Coil Wire-Pallet	16	0	36	IC60-1, N64084-1
FC5DS086BD-PRM	196549	1-3/4in X .086 Screw BDP	Round Head Coil Wire-Pallet	12	0	36	IC60-1, N64084-1
FC5DS099BD-PRM	196563	1-3/4in X .099 Screw BDP	Round Head Coil Wire-Pallet	12	0	36	N64099-1, N70CB-1, N89C-1P
FC6DS084BDPP12	196570	2in X .084 Screw BDP	Round Head Coil Wire-Pallet	12	0	36	IC60-1, N64084-1
FC6DS086BD-PRM	196587	2in X .086 Screw BDP	Round Head Coil Wire-Pallet	9	0	42	IC60-1, N64084-1
FC6DS099BD	681395	2in X .099 Screw BDP	Round Head Coil Wire-Pallet	10.8	0	36	N64099-1, N70CB-1, N89C-1P
FC6DS099BD-PRM	196594	2in X .099 Screw BDP	Round Head Coil Wire-Pallet	9	0	42	N64099-1, N70CB-1, N89C-1P
FC6DS105BD	196600	2in X .105 Screw BDP	Round Head Coil Wire-Pallet	9	0	36	N70CB-1, N80CB-1
FC6DS113BC	196617	2in X .113 Screw BCP	Round Head Coil Wire-Pallet	6	0	48	N70CB-1, N80CB-1
FC7DS086BD-PRM	196624	2-1/4in X .086 Screw BDP	Round Head Coil Wire-Pallet	9	0	36	IC60-1, N64084-1
FC7DS099BD	196631	2-1/4in X .099 Screw BDP	Round Head Coil Wire-Pallet	10.8	0	36	N64099-1, N70CB-1, N89C-1P
FC7DS099BD-PRM	196648	2-1/4in X .099 Screw BDP	Round Head Coil Wire-Pallet	9	0	36	N64099-1, N70CB-1, N89C-1P
FC7DS105BD	196655	2-1/4in X .105 Screw BDP	Round Head Coil Wire-Pallet	6	0	36	N70CB-1, N80CB-1, N89C-1P
FC7DS113BC	196662	2-1/4in X .113 Screw BCP	Round Head Coil Wire-Pallet	6	0	42	N70CB-1, N80CB-1, N89C-1P
FC8DS099BD	196679	2-1/2in X .099 Screw BDP	Round Head Coil Wire-Pallet	7.2	0	42	N64099-1, N70CB-1, N89C-1P
FC8DS099BD-PRM	196686	2-1/2in X .099 Screw BDP	Round Head Coil Wire-Pallet	9	0	36	N64099-1, N70CB-1, N89C-1P
FC8DS113BC	196693	2-1/2in X .113 Screw BCP	Round Head Coil Wire-Pallet	6	0	42	N64099-1, N70CB-1, N89C-1P
FC8DS120BD	196709	2-1/2in X .120 Screw BDP	Round Head Coil Wire-Pallet	5.4	0	42	N80CB-1, N89C-1P, N100C-1, N400C-1
FC9DR120BDP	159636	2-3/4in X .120 Ring BDP	Round Head Coil Wire-Pallet	5.4	0	36	N80CB-1, N89C-1P, N100C-1, N400C-1
FC9DS113BD	159643	2-3/4in X .113 Screw BDP	Round Head Coil Wire-Pallet	6	0	36	N80CB-1, N89C-1P, N100C-1, N400C-1
S SERIES - ROUND HEAD STRIP PLASTIC							
S34S-115B	445287	4-1/2in X .134 Screw DP	Round Head Strip Plastic	1.25	0	96	BIGBERTA160, BRT130
S38-100B	414238	4in X .150 Sm DP	Round Head Strip Plastic	1.25	0	96	
S38-115B	425326	4-1/2in X .150 Sm DP	Round Head Strip Plastic	1.25	0	96	
S38-130B	431686	5-1/8in X .150 Sm DP	Round Head Strip Plastic	1.25	0	60	
S42-130B	484750	5-1/8in X .165 Sm DP	Round Head Strip Plastic	1.25	0	60	
S42-160B	833039	6-1/4in X .165 Sm DP	Round Head Strip Plastic	0.66	0	76	

STAPLE - Tool Selection Guide

Quality staples for every fastening application.

BOSTITCH

INDUSTRIAL

All staples are collated with an adhesive coating that not only holds the staples together, but aids in staple penetration and helps with withdrawal capacity.

Lengths range from 1/8 to 2-1/2 inches. Both light wire and heavy wire staples are available in steel, coated, and stainless steel, and are typically classified by crown width.

Fine wire staples have cross-sectional dimensions.   **Heavy wire staples have gauge sizes.**

CROWN

LEG LENGTH

POINT

Item Number	Reference #	Description	Type	Pack	Case	Skid	Application Tools
15 S4 SERIES: 15-GAUGE 1/2" CROWN STAPLES							
15S4-31G	195856	1-1/4" Leg 1/2" Crown 15ga Flash GAL	Heavy Wire 15 ga.	13.61	0	56	863S4-1
15S4-38G	159339	1-1/2" Leg 1/2" Crown 15ga Flash GAL	Heavy Wire 15 ga.	11.34	0	56	
15S4-44G	181590	1-3/4" Leg 1/2" Crown 15ga Flash GAL	Heavy Wire 15 ga.	9.07	0	0	
15S4-50G	181606	2" Leg 1/2" Crown 15ga Flash GAL itc	Heavy Wire 15 ga.	9.07	0	56	
15S4-57G	159346	2-1/4" Leg 1/2" Crown 15ga Flash GAL	Heavy Wire 15 ga.	6.8	0	70	
15S4-63G	541323	2-1/2" Leg 1/2" Crown 15ga Flash GAL	Heavy Wire 15 ga.	6.8	0	56	
16 S2 SERIES: 16-GAUGE 1" CROWN STAPLES							
16S2-12FG10M	578268	1/2" Leg 1" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	160	438S2-1, 438S2R-1, 450S2-1
16S2-15FG10M	578275	5/8" Leg 1" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	120	
16S2-15SG10M	195559	5/8" Leg 1" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	120	
16S2-19FG10M	167488	3/4" Leg 1" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	108	
16S2-19SG10M	141051	3/4" Leg 1" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	108	
16S2-22FG10M	195863	7/8" Leg 1" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	100	
16S2-22SG10M	195870	7/8" Leg 1" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	100	
16S2-25FG10M	159360	1" Leg 1" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	95	
16S2-25SG10M	115878	1" Leg 1" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	95	
16S2-31FG10M	159377	1-1/4" Leg 1" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	75	
16S2-31SG10M	159384	1-1/4" Leg 1" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	75	
16S2-38FG10M	159391	1-1/2" Leg 1" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	65	
16S2-38SG10M	925595	1-1/2" Leg 1" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	65	
16S2-50SG10M	159407	2" Leg 1" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	54	450S2-1
16 S4 SERIES: 16-GAUGE 1/2" CROWN STAPLES							
16S4-12FG10M	195887	1/2" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	216	438S4-1, 538S4-1
16S4-12SG10M	993563	1/2" Leg 1/2" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	216	
16S4-15FG10M	195894	5/8" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	168	
16S4-19FG10M	159414	3/4" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	144	
16S4-19SG10M	195900	3/4" Leg 1/2" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	144	
16S4-22FG10M	159421	7/8" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	150	
16S4-25FG10M	195917	1" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	125	438S4-1, 538S4-1, 650S4-1
16S4-25SG10M	159438	1" Leg 1/2" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	125	
16S4-28FG10M	174707	1-1/8" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	125	
16S4-31FG10M	159445	1-1/4" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	100	
16S4-31SG10M	159452	1-1/4" Leg 1/2" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	100	
16S4-34FG10M	159469	1-3/8" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	96	
16S4-34SG10M	195924	1-3/8" Leg 1/2" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	96	
16S4-38FG10M	912345	1-1/2" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	80	
16S4-38SG10M	159476	1-1/2" Leg 1/2" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	80	
16S4-38SS-1M	195931	1-1/2" Leg 1/2" Crown 16ga SS	Heavy Wire 16 ga.	10.5	0	675	
16S4-41FG10M	962071	1-5/8" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	72	650S4-1
16S4-41SG10M	195948	1-5/8" Leg 1/2" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	72	
16S4-44FG10M	159483	1-3/4" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	68	
16S4-44SG10M	195955	1-3/4" Leg 1/2" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	68	
16S4-50FG10M	900776	2" Leg 1/2" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	60	
16S4-50SG10M	195962	2" Leg 1/2" Crown 16ga GAL	Heavy Wire 16 ga.	10.08	0	60	

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

Item Number	Reference #	Description	Type	Pack	Case	Skid	Application Tools
16 S5 SERIES: 16-GAUGE 7/16" CROWN STAPLES							
16S5-16FG10M	195979	5/8" Leg 7/16" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.8	0	186	438S5-1, 538S5-1, 650S5-1, 651S5-1
16S5-19FG10M	195986	3/4" Leg 7/16" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.8	0	156	
16S5-22FG10M	195993	7/8"Leg 7/16" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.8	0	126	
16S5-25FG10M	196006	1" Leg 7/16" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.8	0	123	
16S5-25G10M	196013	1" Leg 7/16" Crown 16ga GAL	Heavy Wire 16 ga.	10.8	0	123	
16S5-31FG10M	196020	1-1/4" Leg 7/16" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.8	0	102	
16S5-35FG10M	196044	1-3/8" Leg 7/16" Crown 16ga Flash GAL	Heavy Wire 16 ga.	1	0	90	
16S5-38FG10M	724658	1-1/2" Leg 7/16" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.8	0	84	
16S5-38G10M	196051	1-1/2" Leg 7/16" Crown 16ga GAL	Heavy Wire 16 ga.	1	0	84	
16S5-45FG10M	181620	1-3/4" Leg 7/16" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	72	438S5-1, 538S5-1, 650S5-1, 651S5-1, 750S5-1
16S5-45SG10M	196075	1-3/4" Leg 7/16" Crown 16ga GAL	Heavy Wire 16 ga.	1	0	72	
16S5-50FG10M	159506	2" Leg 7/16" Crown 16ga Flash GAL	Heavy Wire 16 ga.	10.08	0	63	
16S5-50SG10M	196099	2" Leg 7/16" Crown 16ga GAL	Heavy Wire 16 ga.	10.8	0	63	
17 S5 SERIES: 17-GAUGE 7/16" CROWN WIRE STAPLES							
17S5-19G	549371	3/4" Leg 7/16" Crown 17ga Flash GAL	Medium Wire 17ga.	31.68	0	70	438S5-1, 538S5-1, 650S5-1, 651S5-1
17S5-22G	196105	7/8" Leg 7/16" Crown 17ga Flash GAL	Medium Wire 17ga.	28.16	0	56	
17S5-25G	912352	1" Leg 7/16" Crown 17ga Flash GAL it	Medium Wire 17ga.	24.64	0	70	
17S5-28G	549395	1-1/8" Leg 7/16" Crown 17ga Flash GAL	Medium Wire 17 ga.	21.12	0	70	
17S5-31G	549401	1-1/4" Leg 7/16" Crown 17ga Flash GAL	Medium Wire 17 ga.	21.12	0	56	
17S5-34G	549418	1-3/8" Leg 7/16" Crown 17ga Flash GAL	Medium Wire 17 ga.	17.6	0	70	
17S5-38G	449428	1-1/2" Leg 7/16" Crown 17ga Flash GAL	Medium Wire 17 ga.	17.6	0	56	
17S5-41G	313675	1-5/8" Leg 7/16" Crown 17ga Flash GAL	Medium Wire 17 ga.	17.6	0	56	650S5-1, 651S5-1, 750S5-1
17S5-44G	541477	1-3/4" Leg 7/16" Crown 17ga Flash GAL	Medium Wire 17 ga.	14.08	0	70	
17S5-50G	196112	2" Leg 7/16" Crown 17ga Flash GAL it	Medium Wire 17 ga.	14.08	0	56	
1-1/4" WIDE CROWN STAPLES, (.074"x .037"), 5/8" and 3/4" LEGS							
B34C	313736	3/4" Leg 1-1/4" Crown CTN Closing	Carton Closing	2.4	10	360	DS-3219, BTP12180, D19, D19AD3/4
B58C	549494	5/8" Leg 1-1/4" Crown CTN Closing	Carton Closing	2.4	10	420	DS-3219, BTP12180, D19, D19AD
380 SERIES 1/2" CROWN FINE WIRE (.036"x .027") FURNITURE STAPLE (LONG STICK)							
BA-38006LS	550261	1/4" Leg 1/2" Crown 380 Series	Fine Wire -20 ga.	24	8	440	21680B, 21680-ALM
BA-38008LS	196419	5/16" Leg 1/2" Crown 380 Series	Fine Wire 20 ga.	21	8	480	
BA-38010LS	550322	3/8" Leg 1/2" Crown 380 Series	Fine Wire 20 ga.	18	8	432	
BA-38012LS	550339	1/2" Leg 1/2" Crown 380 Series	Fine Wire 20 ga.	15	8	400	
71 SERIES 3/8" CROWN FINE WIRE (.027"x.023") FURNITURE STAPLE							
BA-7106	541552	1/4" Leg 3/8" Crown 71 Series	Fine Wire 22 ga.	25	12	528	21671B, 21671B-ALM, 21671B-LM
BA-7110	549319	3/8" Leg 3/8" Crown 71 Series	Fine Wire 22 ga.	25	10	440	
BA-7110SW	196426	3/8" Leg 3/8" Crown 71 Series	Fine Wire 22 ga.	1	10	440	
BA-7112	549326	1/2" Leg 3/8" Crown 71 Series	Fine Wire 22 ga.	25	8	352	
BA-7112SW	196433	1/2" Leg 3/8" Crown 71 Series	Fine Wire 22 ga.	25	8	352	
BA-7114	549333	9/16" Leg 3/8" Crown 71 Series	Fine Wire 22 ga.	25	8	320	
97 SERIES 3/16" CROWN FINE WIRE (.036"x.027") STAPLE							
BA-9710CLS	549449	3/8" Leg 3/16" Crown 97 Series	Fine Wire 20 ga.	13.3	12	864	S3297, BA-T510, BA-T407, 21697B
1" CROWN, CORRUGATED, 1/2", 3/8" LEG STAPLES							
BA-W12	427969	1/2" Leg, 1" Crown	Corrugated	6.91	0	85	CF15-2
BA-W9	427983	3/8" Leg, 1" Crown W9	Corrugated	9.21	0	85	CF15-2
BCAR U, 3/4" LEG CROWN BEDDING STAPLE							
BCS31P-TAPE	196457	3/4" Leg BCAR 16ga Divergent	U Crown Bedding	29.18	0	80	BCAR1B-495-92L, BCAR-2S
1/2" CROWN, 1" LEG HEAVY WIRE STAPLE							
8DX	448271	1" Leg 1/2" Crown 16ga Divergent	Heavy Wire 16 ga.	24	0	80	438S4-1, 538S4-1, 650S4-1
SB103020 SERIES - 1/2" CROWN, (.103"x.020"), 3/8"- 5/8" PLIER STAPLES							
SB1030201/22M	338920	1/2" Leg 1/2" Crown SB103020 Series GAL	Plier	2.1	20	960	P51-10B
SB1030203/82.9	542481	3/8" Leg 1/2" Crown SB103020 Series GAL	Plier	2.49	20	960	
SB1030205/82.5	290365	5/8" Leg 1/2" Crown SB103020 Series GAL	Plier	2.49	20	840	

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

43

Item Number	Reference #	Description	Type	Pack	Case	Skid	Application Tools
SB5019 SERIES - 1/2" CROWN, (.050"x.019"), 1/2", 3/8", 5/8" PLIER STAPLES							
SB50191/2-6M	549487	1/2" Leg 1/2" Crown SB5019 Series GAL	Plier	6	10	800	
SB50193/8-8M	549470	3/8" Leg 1/2" Crown SB5019 Series GAL	Plier	8.06	10	800	P51-5B
SB50195/8-4M	818784	5/8" Leg 1/2" Crown SB5019 Series GAL	Plier	4	20	1080	
SBNK SERIES - 3/16" CROWN, (.040"x .023"), 5/32" to 9/16" FINE WIRE STAPLE							
SB97-1GLS	442399	1" Leg 3/16" Crown SB97 Series CP	Fine Wire 20 ga.	5	12	864	21697B
9/16" CROWN, 1/4", 3/8" LEG							
SBNK40231/2-10	196877	1/2" Leg 1/2" Crown SBNK Series	Fine Wire	10	20	400	TU20-7, T27-7, T28-11, T31-2, 21684B
SBNK40233/16	196884	3/16" Leg 1/2" Crown SBNK Series	Fine Wire +D4	10	20	1200	TU20-7, T27-7, T28-11, T31-2, 21684B
9/16" CROWN, 1/4", 3/8" LEG							
SCCR251/4	196938	1/4" Leg 9/16" Crown 23ga GAL	Fine Wire 23 ga.	5	20	2380	
SCCR253/8	315181	3/8" Leg 9/16" Crown 23ga GAL	Fine Wire 23 ga.	5	20	1680	
SL SERIES: 5/16" CROWN (.050" x .035"), 1/2" to 1-1/2" LEG							
SL50351-1/2G	345713	1-1/2" Leg 5/16" Crown 18ga GAL	Medium Wire 18 ga.	3	10	600	SL150
SL50351-1/8G	542658	1-1/8" Leg 5/16" Crown 18ga GAL	Medium Wire 18 ga.	3	10	600	S32SL-1, S32SL-OC
SL50351/2G-7M	481551	1/2" Leg 5/16" Crown 18ga GAL	Medium Wire 18 ga.	7	10	600	S32SL-1
SL50351G	542665	1" Leg 5/16" Crown 18ga GAL	Medium Wire 18 ga.	5	10	600	S32SL-1, S32SL-OC
SL50353/4G	427115	3/4" Leg 5/16" Crown 18ga GAL	Medium Wire 18 ga.	5	10	600	S32SL-1, S32SL-OC
SL50355/8G	549357	5/8" Leg 5/16" Crown 18ga GAL	Medium Wire 18 ga.	5	10	800	S32SL-1
SL50357/8G	549364	7/8" Leg 5/16" Crown 18ga GAL	Medium Wire 18 ga.	5	10	480	S32SL-1
3/8", 1/4" LEG STAPLE							
SP191/4	455071	1/4" Leg 3/8" Crown 19ga GAL	Medium Wire 19 ga.	5	40	3840	P3-IND
STCR 2115 SERIES - 7/16" POWERCROWN® STAPLES (.021"x .015") 1/4", 3/8" LEG PLIER STAPLES							
STCR21153/8	542719	3/8" Leg 7/16" Crown STCR 2115 Series	Plier	5	20	2400	B8P(02245)
STCRP21151/4	528499	1/4" Leg 7/16" Crown STCR 2115 Series	Plier	5	100	3600	B8P(02245)
7/16" WIDE CROWN PACKAGING STAPLES, 1/4'', 3/8'' LEG PLIER STAPLES							
STH50191/4-5M	542771	1/4" Leg 7/16" Crown STH 5019 Series	Plier	5.04	20	1260	P6C-8, USO56
STH50193/8-5.8	196945	3/8" Leg 7/16" Crown STH 5019 Series	Plier	5.88	20	1080	P6C-8, USO56
1-3/8" WIDE CROWN STICK PACKAGING STAPLES, (.074 "x .037"), 3/4'', 5/8'' LEG							
SW74373/4	315846	3/4" Leg 1-3/8" Crown SW7437 Series Stick	Carton Closing	2.4	10	360	DS-3522, BTFP12181, D16-2, D16-2AD, F84-138
SW74375/8	449995	5/8" Leg 1-3/8" Crown SW7437 Series Stick	Carton Closing	2.4	10	420	DS-3522, BTFP12181, D16-2, D16-2AD, F84-138
1-3/8" WIDE CROWN STICK PACKAGING STAPLES, (.090"x .040"), 3/4", 5/8'', 7/8'' LEG							
SW90403/4	542795	3/4" Leg 1-3/8" Crown SW9040 Series Stick Pkg	Carton Closing	2	10	360	
SW90405/8	542801	5/8" Leg 1-3/8" Crown SW9040 Series Stick Pkg	Carton Closing	2	10	420	D16-2, D16-2AD, F84-138
SW90407/8	456020	7/8" Leg 1-3/8" Crown SW9040 Series Stick Pkg	Carton Closing	2	10	350	
1-1/4" WIDE CROWN STICK PACKAGING STAPLE, (.090"x .040"), 1-1/2" LEG							
SW9060-112	847135	1-1/2" Leg 1-1/4" Crown SW9060 Series Stick	Carton Closing	4	2	84	BTFP12182
1-3/8" WIDE CROWN COIL PACKAGING STAPLES, (.074"x .037"), 1/2", 5/8'', 3/4" LEG							
SWC74371/2-1M	362147	1/2" Leg 1-3/8" Crown SWC Series Coil Pkg 1M Rolls	Carton Closing	24	0	56	D60ADC, D61ADC, D62ADC
SWC74371/2-4M	999988	1/2" Leg 1-3/8" Crown SWC Series Coil Pkg 4M Rolls	Carton Closing	24	0	54	FC95EC Box Machine, FC96EC Box Machine
SWC74373/4-1M	240646	3/4" Leg 1-3/8" Crown SWC Series Coil Pkg 1M Rolls	Carton Closing	24	0	56	D60ADC, D61ADC, D62ADC
SWC74373/4-4M	542849	3/4" Leg 1-3/8" Crown SWC Series Coil Pkg 4M Rolls	Carton Closing	24	0	54	FC95EC Box Machine, FC96EC Box Machine
SWC74375/8-1M	521810	5/8" Leg 1-3/8" Crown SWC Series Coil Pkg 1M Rolls	Carton Closing	24	0	56	D60ADC, D61ADC, D62ADC
SWC74375/8-4M	196952	5/8" Leg 1-3/8" Crown SWC Series Coil Pkg 4M Rolls	Carton Closing	24	0	54	FC95EC Box Machine, FC96EC Box Machine
7/32" CROWN 18-GAUGE (.050"x.035") STAPLE, 1/4" - 1-1/2" LEG							
SX50351-1/8DP	196969	1-1/8" Leg 7/32" Crown 18ga	Medium Wire - 18ga.	3	10	800	S32SX-1 Series, SB150SX

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

RING DESCRIPTORS

AL=Aluminum   BT=Blunt Tip (nothing means sharp tips)   RG and G=Regular Galvanized
BB=Brite Basic   HTGL=Hi-Tensile Galvanized   SS=Stainless

	TOOLS	RING TYPE	WIRE SIZE	RING SIZE	CLOSURE SIZE (I.D. MIN.-MAX.)	RING PART	RING DESCRIPTION	RING/ PACK	PACK/ CASE	CASE/ SKID
1	SC73462	C	16 GA	3/8''	1/16''-1/18'', 1.6-3.2mm	RING316AL130B	3/32 16GA AL CRING BT	13000	1	100
2	SC760, SC760CT, SC761	C	16 GA	1/2''	SC760, SC760CT: 1/8''-7/32'', 3.2-5.6mm, SC761: 3/16''-7/32'', 4.8-5.6mm	RING516G100	1/2 16GA GL CRING	10000	1	100
						RING516G100B	1/2 16GA GL CRING BT	10000	1	100
						RING516SS100	1/2 16GA SS CRING	10000	1	100
						RING516SS100B	1/2 16GA SS CRING BT	10000	1	100
3	SC7, SC7C, SC7E, SC77XE	C	15 GA	3/4''	SC7, SC7E , SC77XE, SC4LWH: 5/16''-27/64'', 7.9-10.7mm SC7C: 3/16''-11/32'', 4.8-8.7mm	RING15100B	3/4 15GA BB CRING BT	10000	1	100
						RING15100P	3/4 15GA BB CRING	10000	1	100
						RING15G100B	3/4 15GA GL CRING BT	10000	1	100
						RING15G100P	3/4 15GA GL CRING	10000	1	100
						RING15SS100B	3/4 15G SS CRING BT	10000	1	100
4	SC742, SC743,	C	16 GA	3/4''	SC742 (Short Mag.), SC743: 3/16''-11/32'', 4.8-8.7mm	RING16G110	3/4 16GA GL CRING	11000	1	100
						RING16G110B	3/4 16GA GL CRING BT	11000	1	100
						RING16SS110	3/4 16GA SS CRING	11000	1	100
5	TR201, TR203, TR315	D	15 GA	3/4''	1/4''-3/8'', 6.4-9.6mm	RINGSR15	3/4 15GA BB BOST DRING	10000	1	100
						RINGSR15SS	3/4 15GA SS BOST DRING	1000	1	100
6	RINGER9/16	D	16 GA	9/16''	3/16'', 4.8mm	RINGR15G50	9/16 15GA GL DRING	2500	10	60
						RINGR15G50B	9/16 15GA GL DRING BT	2500	10	60
						RINGR15SS50	9/16 15GA SS DRING	2500	10	60
						RINGR15SS50B	9/16 15GA SS DRING BT	2500	10	60
7	P7	C	16 GA	11/16''	9/32'' - 23/64'', 7.1mm- 9.1mm	RING616G50	1/2 16GA GL CRING	2500	10	60
						RING616G50B	1/2 16GA GL CRING BT	2500	10	60
						RING616SS50	1/2 16GA SS CRING	2500	10	60
8	HFP9	D	9 GA	1-3/16''	7/16'', 1.1mm	RING09AL25	1 1/2 9GA AL DRING BT	2500	1	100
9	SC50T, SC50HP	C	11 GA	1-1/2''	9/16''-5/8'', 14.3-15.9mm	RING11AL40	1 1/2 11GA AL CRING	1600	1	96
						RING11RG40	1 1/2 11GA RGL CRING	1600	1	96
						RING11RG40B	1 1/2 11GA RGL CRING BT	1600	1	96
						RING11SS40	1 1/2 11GA SS CRING	1600	1	96

ADDITIONAL RINGS

RING PART	DESCRIPTION	RING/PACK	PACK/CASE	CASE/SKID
RING516N50P	1/2 16G BB DRING	10,000	1	100
RINGCC16G10M	3/4 16G BB CONT. COIL CRING	10,000	13	4
RINGCC16SS10M	3/4 16G SS CONT. COIL CRING	10,000	13	4
RINGHR14SS	14MM 17GA SS DRING	10,000	1	100
RING14NSPHR	3/4 14G BB SUPER POLISHED DRING LOOSE	11,000	Rings/25lbs box	
RING315AL100	3/32 15G AL CRING	10,000	1	100
RING1714G100S	1-1/16 14GA CL CRING BT	5,000	1	100

BOSTITCH®

INDUSTRIAL

TOOL DESCRIPTORS
C=Tight Closure   E=Extended Nose   XE=Extra, Extended Nose

SUGGESTED APPLICATIONS

Small bag closure, picture wire, small caging, arts and crafts, cords, cables, light wire to wire

Bungee (w/SC760), oil absorption socks, small dia. auto controls, small rope, bag closure and elec. strain relief

Bungee (w/SC760), oil absorption socks, small dia. auto controls

Insulation, lobster bait bag, cargo nets

Bag closure, netting, bait bag, traps, pots and cages (crab, eel, shrimp, lobster, mink, bird, ect)

Automotive seating, bagging, bungee (w/SC7C)

Bedding (ticking to innerspring/borderwire, pocketed coils), auto seats, upholstery

Bungee, caging, auto control cables, ropes

Automotive seating

Caging, insulation, silt fence, rope tying

Nursery (root ball), caging, auto seats, bedding

Bagging, oil socks, novelty items, components

Lobster trap heads (w/SC742 short mag.), bait bag (w/SC742), insulation, novelty/components

Lobster traps heads (w/SC742 short mag.), bait bag, insulation, novelty/components

Furniture, bedding, ticking to innerspring

Novelty, components

Nursery pot tagging, crafts, bag closure

Tagging, bagging

Trap and cage repair

Lobster traps heads, bait bags

Nursery (root ball, pot tagging), bagging, crafts

Bagging, crafts

Bird control netting

Fence tensioning wire, signs, mending, bundling, bagging, crafts, stringing lights

Garland on wire, component assembly

Fencing/large bagging, stringing lights and garland to wire

Fencing, large bagging, concrete reinforcement wire, rubber tree staking (nursery)

Concertina wire, control cables

Garland, lighting (stringing on wire), electrical cable strain relief, rope to mesh, bungee cords

Oil absorption socks

Ring size reference diagrams:

1. 3/8'' — 1/16'' min
2. 1/2'' SC760 / SC761 — 1/8'' min — 3/16'' min
3. 3/4'' SC7C / SC7 etc. — 3/16'' min — 5/16'' min
4. 3/4'' SC742/743 / SC742SG — 3/16'' min — 5/16'' min
5. 3/4'' — 1/4'' min
6. 9/16'' — 3/16'' min
7. 11/16'' — 9/32'' min
8. 1 3/16'' — 7/16'' min
9. 1 1/2'' — 9/16'' min

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

Item Number	Ref #	Description | Weight	Page Number
BT35B-3	548800	18ga Brad Nailer 5/8"– 1-3/8" | 3.44 lbs	15, 17, 22, 27
BT50B-1	850524	18ga Brad Nailer 1-3/8"– 2" | 3.18 lbs	15, 17, 22, 27
BT50B-3	549067	18ga Brad Nailer 1-3/8"– 2" | 3.6 lbs	15, 17, 22, 27
BTFP12180	196471	Manual Stapler 1-1/4" Crown 3/4"– 5/8" | 7.33 lbs	33
BTFP12181	196488	Manual Stapler 1-3/8" Crown 5/8"– 7/8" | 7.32 lbs	33
BTFP12182	847142	Air Stapler 1-1/2" Crown 1-1/2" | 17.51 lbs	33
CF15-2	427952	Stapler Corrugated 1" Crown 3/8"– 5/8" | 7.02 lbs	11, 17, 28
D62ADC	469443	Packaging SWC Coil Stapler 1/2"– 3/4" | 6.68 lbs	33, 34
DS-3219	630577	Packaging C Series Stick Stapler 5/8"– 3/4" | 7.31 lbs	33
DS-3522	779672	Packaging SW74/90 Series Stick Stapler 5/8"– 7/8" | 6.9 lbs	33
ESD-450S2P	424746	1" 16ga Stapler 6 Layer Clinching 1/2"– 2" | 10.1 lbs	34
F84-138	993525	Stapler 1-3/8" Crown with plates for SW74 & SW90 Series 5/8"-7/8" | 88.33 lbs	35
FC96EC	817404	Packaging SWC Coil Stapler 1/2"– 3/4" | 250 lbs	35
HFP9	543099	9ga D-Ring Stapler 7/16" | 1.64 lbs	11, 32, 36, 38
IC60-1	744984	.080 X .090 Coil Nailer 1"– 2-3/8" | 7.1 lbs	10, 20, 24, 28, 37, 45
JB600	851965	STCR Series Stapler 7/16" Crown 1/4"– 9/16" | 2.81 lbs	31
N100C-1	261078	.099-.162 Angle Coil Nailer 1-1/2"– 4" | 13.34 lbs	10
N64084-1	381004	.084 Angle Coil Nailer 1-1/4"– 2-1/2" | 8.22 lbs	10, 22
N64099-1	381011	.099 Angle Coil Nailer 1-1/4"– 2-1/2" | 8.29 lbs	10, 22
N70CB-1	447103	.099 Angle Coil Nailer 1-1/2"– 2-3/4" | 9.95 lbs	10, 22
N70CBPAL	545403	.099 Angle Coil Nailer Mounted 1-1/2"– 2-3/4" | 8.41 lbs	10
N89C-1P	167587	.099-.148 Nailer 2"– 3-1/4" | 9.91 lbs	11, 20
P3-IND	491635	SP191/4 Series Stapler 1/4"– 3/8" | 0.6 lbs	31
P51-10B	684587	Stapler SB103020 Series 1/2" Crown 3/8"– 5/8" Leg | 7.19 lbs	34
P51-5B	678661	SB5019 Series Stapler 1/2" Crown 3/8"– 5/8" | 6.55 lbs	34

Item Number	Ref #	Description | Weight	Page Number
P6C-6	480926	STCR2619 Series Stapler 1/4"– 3/8" | 1.11 lbs	31
P6C-8	733220	STCR5019 Series Stapler 1/4"– 3/8" | 1.13 lbs	31
P6C-8P	475055	P-Point Blade Stapler 3/4" Crown 1/4"– 3/8" | 1.13 lbs	31
P7	594005	16ga Stapler 9/32" Closed C-Ring | 0.8 lbs	31
RINGER9/16	196846	16ga Stapler 3/16" Closed D-Ring 9/16" | 1.24 lbs	38, 39, 46
S32SL-1	549098	18ga Stapler 5/16" Crown 1/2"– 1-3/8" | 3.4 lbs	15, 17, 22, 27
S32SL-OC	196853	18ga Stapler 5/16" Crown Outward Clinch 5/8"– 1-3/8" | 3.6 lbs	25
S32SX-1	549081	18ga Stapler 7/32" Crown 1/2"– 1-1/2" | 3.4 lbs	15, 17, 22, 27
SC50HP	196891	11ga Stapler Manual 9/16" Closed C-Ring 1-1/2" | 10.6 lbs	37, 38, 39
SC50T	196907	11ga Stapler Air 9/16" Closed C-Ring 1-1/2" | 24.39 lbs	32, 37, 39
SC7	952327	15ga Stapler 5/16" Closed C-Ring 3/4" | 3.88 lbs	24, 30, 32, 37, 38, 39, 46
SC73462	159773	16ga Stapler 1/16"-1/8" Closed C-Ring 3/8" | 3.86 lbs	32, 36
SC73462A	196914	16ga Stapler 3/8" C-Ring | 5 lbs	32, 36, 46
SC742	167938	16ga Stapler 3/16" Closed C-Ring 3/4" | 4.28 lbs	36, 38, 39, 46
SC743	462925	16ga Stapler 3/16" Closed C-Ring 3/4" | 3.87 lbs	32, 36, 39, 46
SC760	374362	16ga Stapler 1/8" Closed C-Ring 1/2" | 3.96 lbs	32, 38, 46
SC761	127192	16ga Stapler 3/16" Closed C-Ring 1/2" | 3.94 lbs	31, 39, 46
SC77XE	905514	15ga Stapler Long Nose 5/16" Closed C-Ring 3/4" | 4.27 lbs	37, 46
SC7C	543334	15ga Stapler 3/16" Closed C-Ring 3/4" | 3.91 lbs	39, 32, 46
SC7E	196921	15ga Stapler Extended Nose 3/16" Closed C-Ring 3/4" | 3.94 lbs	37, 46
TR201	963347	15ga Stapler Spring Return Reg Magazine D-Ring 3/4" | 4.19 lbs	15, 25, 32, 46
TR203	807993	15ga Stapler Spring Return Long Magazine D-Ring 3/4" | 4.33 lbs	15, 25, 32, 46
TR315	182832	15ga Stapler Air Return High Speed Long Magazine D-Ring 3/4" | 4.55 lbs	15, 25, 32, 46
USO56-1	471224	STCR5019 Series Stapler 7/16" Crown 1/4"-9/16" | 3.27 lbs	21

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

Work Safely with Tools, Wear Safety Glasses. For more information on contact, sequential, trigger operated or auto fire see safety information on page 3.

51

BOSTITCH®
INDUSTRIAL